

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Tenneco Oil Company
3. ADDRESS OF OPERATOR  
720 S. Colorado Blvd., Denver, CO 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1020' FNL and 1510' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO:                      | SUBSEQUENT REPORT OF:    |
|---|--------------------------|
| TEST WATER SHUT-OFF <input type="checkbox"/>  | <input type="checkbox"/> |
| FRACTURE TREAT <input type="checkbox"/>       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE <input type="checkbox"/>     | <input type="checkbox"/> |
| REPAIR WELL <input type="checkbox"/>          | <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE <input type="checkbox"/>    | <input type="checkbox"/> |
| CHANGE ZONES <input type="checkbox"/>         | <input type="checkbox"/> |
| ABANDON* <input type="checkbox"/>             | <input type="checkbox"/> |

(other) Change Drilling Program

to utilize gas rather than mud-laden fluid for well control

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We propose to drill using the following parameters

- 1) Drill 13 3/4" hole to + 250'
- 2) Run 9 5/8" csg and cement with sufficient cement to circulate
- 3) Drill 8 3/4" hole to + 3000'
- 4) Run 7" csg and cement with sufficient cement to circulate to surface
- 5) Drill 6 1/4" hole to T.D. @ + 6700' with gas
- 6) Log well
- 7) Run 4 1/2" csg to T.D. and 2 stage cement back to surface

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley Statten TITLE Admin. Supervisor DATE 11/4/79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: