

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other2. NAME OF OPERATOR  
DOME PETROLEUM CORP.3. ADDRESS OF OPERATOR 501 Airport Drive  
Suite 107, Farmington, New Mexico 874014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 820' FSL, 1850' FEL  
AT TOP PRCD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐

(other) RUN PRODUCTION CASING

5. LEASE

NM 14973

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DOME FEDERAL 7-27-13

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

WAW FRUITLAND - PICTURED CLIFF

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 7, T27N, R13W

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6006 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to 1456'. Ran 47 jts., 1443', 2 7/8", 6.5# J-55 EUE casing. Casing landed at 1443' GL. Cemented with 125 sacks 65/35 Pozmix with 6% Gel and 1/4# Floseal/sack. Followed with 50 sacks class "B" cement with 2% CaCl and 1/4# Floseal/sack. Plug down at 4:00 PM, 07/13/79. Circulated cement.

RECEIVED

JUL 20 1979

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.JUL 23 1979  
U. S. GEOLOGICAL SURVEY  
DIST. 3

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE DRILLING FOREMAN DATE July 16, 1979

H. D. HOLLINGSWORTH

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY

\*See Instructions on Reverse Side

Nymoc

APPROVED

JUL 20 1979

ACTING DISTRICT ENGINEER