

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

DOME PETROLEUM CORP.

3. ADDRESS OF OPERATOR 501 Airport Drive
Suite 107, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 820' FSL, 1850' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐ SPJD AND SET SURFACE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 8 3/4" hole at 10:30 AM 07/03/79. Drilled to 46'. Ran 1 jt. 7", 20#, K55, ST & C casing. Casing landed at 42' GL. Cemented with 35 sacks class "B" cement with 2% CaCl. Plug down at 1:00 PM, 07/03/79. Circulated cement.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED

JUL 20 1979

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

H.D. HOLLINGSWORTH

TITLE DRILLING FOREMAN

DATE July 11, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

*See Instructions on Reverse Side

APPROVED

JUL 23 1979

ACTING DISTRICT ENGINEER

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other2. NAME OF OPERATOR =
DOME PETROLEUM CORPORATION3. ADDRESS OF OPERATOR 501 Airport Drive
Suite 107, Farmington, New Mexico 874014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1490' FNL, 800' FWL
AT TOP PRCD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) RUN PRODUCTION CASING

5. LEASE

M 8409

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

DOME FEDERAL 7-27-13

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

WAW PICTURED CLIFF

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 7, T27N, R13W

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5959 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 1410'. Ran 46 joints (1407') 2 7/8", 6.5#, J-55 casing. Casing landed at 1407' GL.

Cemented with 115 sacks 65/35 Pozmix with 6% gel and 1/4# Floseal/sack.

Followed with 50 sacks class "B" cement with 2% CaCl and 1/4# Floseal/sack.

Plug down at 1:30 pm, 05/22/79. Circulated cement.

Subsurface Safety Valve: Manu. and Type

Set @ ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLTINGSWORTH TITLE DRILLING FOREMAN DATE 05/23/79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

