UNITED STATES

UNITED STATES	E 15405
DEPARTMENT OF THE INTERIOR	5. LEASE
	USA -NM-013860-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OUNDRY MOTION	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	
to the such proposals.)	8. FARM OR LEASE NAME
1. oil gas well other	Russell Com
- Volley	9. WELL NO.
2. NAME OF OPERATOR	1 8 8 8 8 2 9
Tenneco Oil Company	
3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME
720 S. Colorado Blvd., Denver, CO 80222	<u>Basin Dakota</u>
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OF
below.)	AKEA AREA (企業分割)
AT SURFACE: 1080'FSL & 815'FWL, Unit M	Sec. 23. T28N PRW 33.33
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico
16 CHECK APPROPRIATE BOY TO	14. API NO. 국소소국 급
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	5854 GL Service States
TEST WATER SHUT-OFF	9991 UE 1
FRACTURE TREAT	ការប្រជាជាធិប្បាធិប្បធានា មិន្ត្រី មាន មិន្ត្រី មាន មិន្ត្រី មាន មិន្ត្រី មាន មិន្ត្រី មាន មិន្ត្រី មាន មិន្ត្រ មាន មិន្ត្រី មាន មិ
SHOOT OR ACIDIZE	<u> </u>
REPAIR WELL	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	change on Form 9–330.)
CHANGE ZONES	기 기계
ABANDON*	그 그 그를 가득했다면 이번 통경으로 살
(other) Spud, surface, production csg	ର
17. DESCRIBE PROPOSED OF COMPLETED COMP	<u> 한 </u> 어떻을까지 뭐 경우되면 뭐
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is directly measured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates.
measured and true vertical depths for all markers and zones pertinent	ectionally drilled, give subsurface locations and
10/16/79-10/29/79	to this work.)
==, 10, 13 10, 23, 13	그 사람들은 사람들이 되는 사람들이 되었다.
Shudded 121" holo and dust 17. 14. oosy	ម៉ូនិក្ស៊ីពី 🛒 🚉 និមិ
Spudded 12½" hole and drilled to 225'. Ran 5 @ 222'. Cemented w/200 sx regular w/2% CACL2	jts. 9 5/8" 36# K-55 csg % set
@ 222'. Cemented w/200 sx regular w/2% CACL2.	WOC 12 hrs. Tested BOF &
csg to 600 PSI for 15 min. Held ok. Drilled 8 of 7" csg to 2998'. Cmt w/500sxs of Bi-lite 1	3/4" hole to 3000' Ran 74 its
of 7" csg to 2998'. Cmt w/500sxs of BJ-lite, 1 Circ. cmt to surface. WOC 12 hrs. NU. Podused	150 sxs neat, and 2% CACL2 pn
Circ. cmt to surface. WOC 12 hrs. NU. Reduced 6890 on 10/25. Ran electric logs. Ban 41	hole to 65" and drilled to
to cond hole. Reamed hole to TD.Ran 92 jts of w/TOL @ 2890'. Cmt w/500 sys of 50/50 parmin	45" CSG W/TIW linon to 60001
w/TOL @ 2890'. Cmt w/500 sxs of 50/50 Pozmix.	Released via Work
	Mercasea rig. Wood.
Subsurface Safety Valve: Manu. and Type	
	Set @Ft.
18. I hereby certify that the foregoing is true and correct	TO THE STATE OF TH
SIGNED CHALLY MANUELLE Admin. Supervis	* " " " " " " " " " " " " " " " " " " "
TITLE TOUTTH Souber V 12	DATE
(This space for Federal or State office of	use)
APPROVED BY	PODOVED
CONDITIONS OF APPROVAL, IF ANY:	DATE APPRUATO
NMOCC	
Miloo	NOV 29 1979 0 A

*See Instructions on Reverse Side

JAMES F. SIMS

GAS SUPERVICOR