UNITED STATES

UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	NM-03605	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAM	E Marron
1. oil gas 🖾 other	9. WELL NO.	
2. NAME OF OPERATOR	95	
WILLIAM C. RUSSELL	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Largo Chacra	
745 Fifth Avenue, N.Y., N.Y. 10022	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 23, T27N-R8W, NMPM	
below.) 1980 FSL-1950 FWL AT SURFACE:	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: -same-	San Juan	New Mexico
AT TOTAL DEPTH: -same-	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-045-23626	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5931' GR	
TEST WATER SHUT-OFF	(NOTE: Report results of mi change on Form 9	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	irectionally drilled, give suc	give pertinent dates
Spudded: 9-28-80 124" Hole - 8 5/8" surface x 242' x 24# 300 sacks cement - circulated		
TD: $10-3-80$ 7 7/8" hole x 3360 " - $4\frac{1}{2}$ " casing x 11.6 # x 3330 ' 1200 sacks cement - circulated		
Perfs. one per ft.: 3056-62, 3082-02, 3218-22		
Sand-water frac: $100,000 \text{m} \times 20 - 40 \text{sand}$, $100,000 \text{gals}$. water Tubing: $1\frac{1}{2}$ " EUE x 3105 ' (11-15-80)		
- azing: 12 202 k 3103 (11 13 00)		
	•	•
Subsurface Safety Valve: Manu. and Type	Set	@ Ft.
18. I have by cortify that the foregoing is true and correct		
	DATE12-2	2-80
(This space for Federal or State office use)		
APPROVED BY		
CONDITIONS OF APPROVAL, IF ANY: JAN 0 8 1981		
DHILL O DOL		

*See Instructions on Reverse Side