

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well ☐ gas well ☒ other ☐  
2. NAME OF OPERATOR  
Supron Energy Corporation  
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1190 Ft./N; 790 ft./W line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐


SUBSEQUENT REPORT OF:



5. LEASE  
I-149-IND-8468  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo Indian  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Navajo "B"  
9. WELL NO.  
6-M  
10. FIELD OR WILDCAT NAME  
Basin Dakota - Blanco Mesaverde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 19, T-27N, R-8W  
N.M.P.M.  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6016 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- Spudded 12-1/4" hole at 6:30 p.m. 2-1-80.
- Drilled 12-1/4" surface hole to total depth of 266 ft. R.K.B.
- Ran 6 joints (248 ft.) of 8-5/8", 24.00#, K-55 casing. Landed at 261 ft. R.K.B.
- Cemented with 205 sacks of class "B" with 2% Calcium Chloride. Plug down at 9:00 a.m. 2-2-80. Cement circulated to surface.
- Waited on cement 12 hours.
- Pressure-tested casing to 1000 psi for 15 minutes.



(CORRECTED COPY)

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE March 19, 1980  
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

\*See Instructions on Reverse Side

MAR 20 1980

FARMINGTON DISTRICT  
BY M. L. Luchera