5. LEASE

NOO-C-14-20-7472

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| GEOLOGICAL SURVEY | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Allotted | |
|---|---|---|--|
| (Do not use th | RY NOTICES AND REPORTS ON WELLS his form for proposals to drill or to deepen or plug back to a different Form 9-331-C for such proposals.) | 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME | |
| 1. oil well | gas X other | Da On Pah 3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 | |
| 2. NAME | OF OPERATOR | 1 4 \$ 4 \$ 5 \$ \$ \$ \$ \$ \$ | |
| J. Gregory Merrion & Robert L. Bayless 3. ADDRESS OF OPERATOR P.O. Box 1541, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1900 FNL & 1050 FEL AT TOP PROD. INTERVAL: same AT TOTAL DEPTH: same | | WAW Fr./Pic. Cliffs: | |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR | |
| | | Sec. 35, T27N, R12W 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 | |
| | | 12. COUNTY OR PARISH 13. STATE | |
| | | San Juan - 1 N.M. 1 1 14. API NO. 11. 11. 11. 11. 11. 11. 11. 11. 11. 1 | |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF | | 17. Al 10. 12.7 \$ 12.7 \$ 12.5 \$ | |
| | | 15. ELEVATIONS (SHOW DF, KDB, AND WD) | |
| | | 5950' GL | |
| | | 그 그 그 그 그 그를 일 함께 그 위 그 뭐 그 작은 작은 | |
| FRACTURE SHOOT OR | | | |
| REPAIR WE | LL | (NOTE: Report results of multiple completion or zone change on Form 9-330.) | |
| MULTIPLE (| COMPLETE 🗍 🗒 | | |
| CHANGE ZONES | | | |
| (other) S | pud, surface csg., cement | | |
| includir | IBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating estimated date of starting any proposed work. If well is dired and true vertical depths for all markers and zones pertinent. L & B Speed Drill spud 9-3/4" hole to 9 23 lb./ft. surface casing @ 93' w/50 sa | irectionally drilled, give subsurface locations and it to this work.)* 3 ft. Set 91.8 ft. of 7", | |
| 3-06-80 | Drilling. | | |
| 3-08-80 | TD @ 1285 ft. Ran 1285 ft. of 4-1/2", 100 sacks econofill (9.9 gals./sack yei (5.6 gals./sack yeilding 1.18 sacks). WOCT. | 9.5 lb./ft casing. Cemented wit ilding 1.60 gacks ne Circular Cement back to surface | |
| | | CON. COM | |
| | Safety Valve: Manu. and Type | DIST. 3 Ft. | |
| 18. I hereby | y certify that the foregoing is true and correct | | |
| SIGNED / | TITLE Operator | DATE March 14, 1980 | |
| | | | |
| | (This space for Federal or State off | ice use) | |

MNOCCI

MAR 19 1980