

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1645' S, 1790'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

RECEIVED

MAY 28 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF 078390
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Jones A
9. WELL NO.
4A
10. FIELD OR WILDCAT NAME
S. Blanco PC Ext. & Blanco MV
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13, T-28-N, R-8-W
N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6310' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-15-80: PBTD 5580'. Tested casing to 3500#, OK. Perfed P.L. 5128,5134,5140,5157,5163, 5169,5198,5232,5247,5259,5317,5351,5390,5407,5425,5442,5477,5496' W/1 SPZ. Fraced w/ 60,000# 20/40 sand, 120,000 gal. wtr. Flushed w/ 6594 gal. wtr. Perfed C.H. & Men. 4541,4547,4567,4572,4583,4614,4630,4637,4644,4651,4821,4830, 4859,4923,4971,4977,5025' W/1 SPZ. Fraced w/ 61,000# 20/40 sand, 122,000 gal. wtr. Flushed w/ 6216 gal. wtr. Perfed P.C. 2905-2926,2953-2975,2995-3006' w/16 SPZ. Fraced w/56,000# 10/20 sand, 61,000 gal. wtr. Dropped 2 sets of 16 balls each. Flushed w/ 4929 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Lisco TITLE Drilling Clerk DATE May 20, 1980

(This space for Federal or State use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NM0000

ACCEPTED FOR RECORD
MAY 30 1980
FARMINGTON DISTRICT
BY 98