UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	LEASE	
	SF 077	123

		- ,		-
6 1	FINE	141	LA L	LOTTEE OR TRIBE NAM

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a differe reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas x other	Warren
Well Well Oddo	9. WELL NO.
2. NAME OF OPERATOR El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco Mesa Verde
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	
below.) AT SURFACE: 1850'S 1850'E	N.M.P.M. 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 1850'S, 1850'E AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	5943' GL
TEST WATER SHUT-OFF	$\sigma \setminus \sigma$
TEST WATER SHUT-OFF SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
500 on 11750 oncurs = 1	change on Form 9–330.)
MULTIPLE COMPLETE	SURVET \
MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) FEB 4 FEB	1. W.
(other) FARNITY	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly s including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones perting	s directionally drilled, give subsurface locations and
-17-80: PBTD 4972'. Tested casing to 3500#, C 4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr.	OK. Perfed P.L. 4526,4551,4557,4571,
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra	OK. Perfed P.L. 4526,4551,4557,4571, 49,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr. Perfed Men. 4182,4188,4237,4242,4261,4 W/1 SPZ. Fraced w/34,172# 20/40 sand,	OK. Perfed P.L. 4526,4551,4557,4571, 49,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr. Perfed Men. 4182,4188,4237,4242,4261,4 W/1 SPZ. Fraced w/34,172# 20/40 sand,	OK. Perfed P.L. 4526,4551,4557,4571, 49,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr. Perfed Men. 4182,4188,4237,4242,4261,4 W/1 SPZ. Fraced w/34,172# 20/40 sand, gal. wtr. Subsurface Safety Valve: Manu. and Type	OK. Perfed P.L. 4526,4551,4557,4571, 19,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga 4265,4350,4358,4370,4374,4489,4493' 64,218 gal. wtr. Flushed w/5502 FEB 25 1980 ORET CON. COM. DIST. 3
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr. Perfed Men. 4182,4188,4237,4242,4261,4 W/1 SPZ. Fraced w/34,172# 20/40 sand, gal. wtr. Subsurface Safety Valve: Manu. and Type	OK. Perfed P.L. 4526,4551,4557,4571, 19,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga 4265,4350,4358,4370,4374,4489,4493' 64,218 gal. wtr. Flushed w/5502 FEB 25 1980 ORET CON. COM. DIST. 3
4577,4583,4592,4596,4628,4633,4639,464 4818,4832,4848,4877,4918' W/1 SPZ. Fra wtr. Flushed w/5586 gal. wtr. Perfed Men. 4182,4188,4237,4242,4261,4 W/1 SPZ. Fraced w/34,172# 20/40 sand, gal. wtr. Subsurface Safety Valve: Manu. and Type	OK. Perfed P.L. 4526,4551,4557,4571, 19,4663,4668,4694,4710,4729,4751,4784 aced w/71,725# 20/40 sand, 141,456 ga 4265,4350,4358,4370,4374,4489,4493' 64,218 gal. wtr. Flushed w/5502 FEB 25 1980 ON: COM. DIST. 3 February 19, 1980 acoffice use)

*See Instructions on Reverse Side

FEB 22 1980

8.76 m. 16.44. s

BY ML Ruchera