

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1180' N, 1815' W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE SF 078390	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Jones A	
9. WELL NO. 5A	
10. FIELD OR WILDCAT NAME Blanco MV; Blanco PC Ext.	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T-28-N, R-8-W N.M.P.M.	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6363' GL	

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

X

RECEIVED

APR 15 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. H.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-7-80: PBTD 5614'. Tested casing to 3500#, OK. Perfed Upper & Lower P.L.
5161,5190,5193,5195,5198,5200,5216,5219,5222,5225,5228,5251,5253,
5264,5269,5272,5274,5304,5310,5368,5405,5429,5440,5446,5462,5479,
5530,5548,5617' W/1 SPZ. Fraced w/73,500# 20/40 sand,147,000 gal.
wtr. Flushed w/ 6700 gal. wtr. Perfed C.H. & Men. 4494,4591,
4597,4603,4618,4624,4630,4658,4675,4681,4687,4693,4844,4853,4901,
4907,4978,5008,5097' W/1 SPZ. Fraced w/ 63,500# 20/40 sand,127,000
gal. wtr. Flushed w/6250 gal.wtr.

Perfed P.C. 2970-2985,3010-3030,3050-3070,3078-3085' W/16 SPZ.
Fraced w/ 60,000 10/20 sand, 67,500 gal. wtr. Flushed w/5500
gal. wtr. Dropped 3 sets of 16 balls each.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Al D. Fusco TITLE Drilling Clerk DATE April 8 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

r. Flushed W/5500
 RECEIVED
 APR 17 1980
 April 8, 1980
 OIL CON. COM.
 DIST 3
 AGREEMENT FOR RECORD

APR 16 1980

BY E. B. Baker

NMOCC

***See Instructions on Reverse Side**