

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
720 S. Colorado Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 955' FSL; 1770' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE

SF - 078390

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Price

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13 T28N R8W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6318 gl.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
9/13/80.

MIRUSU. RIH w/2 7/8" Bit. Tagged cmt. @ 7350'. Drilled to PBTD @ 7443'. Circ'd. hole w/1% KCL water. Spot 500 gals 7 1/2% HCL over perms. Perfd. (2 JSPF) Dakota 7172-92', 7264-68', 7298-7306', 7330-38', 7366-68', 7380-84'. Acidized down csg. w/1850 gals 15% HCL & 138 balls. @ 35 BPM. Frac'd Dakota w/80,000 gals. 30# XL gel containing 80,000# 20/40 sand & 25,000# 10/20 sand in 2 stages. w/46 balls between stages. Tagged frac sand w/35 millicuries of radioactive sand. Clean out to PBTD. Tagged sand @ 7317'. Pulled up 8 jts. & landed tbg @ 7191'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carly V. Hatten TITLE Asst. Div. Admin. Mgr. DATE September 29, 1980

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Oct 8 1980

BY BW FARMINGTON DISTRICT

*See Instructions on Reverse Side