

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1710'GSL & 975'FWL, Unit L
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Status Report: Drilling

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

FEB 4 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF-078499
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Tapp
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 16; T28N; R8W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5920'GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/4/80-

Spud 13 3/4" hole on 1/4/80. Ran 5 jts of 9 5/8", 36# csg and set @ 230'. Cmt. w/140 sxs CLB w/2% CACL2. Circ. to surface. Reduced hole to 7 7/8" & resumed drilling. On 1/8, ran & set 84 jts of 7", 23# csg @ 3400'. Cmt. w/600sxs of 50/50 Pozmix & 4% gel & 6 1/4#/sk Gilsonite & 1/4#/sk Cellaflake. Tailed in w/750 sxs CLB & 2% CACL2. Circ. cmt to surface. Ran & set 197 jts of 4 1/2", 10.5# & 11.6#csg set @ 6816'. Cmt w/200 sxs 50/50 Pozmix, 4% gel, 0.4% D-13 followed by 100sxs CLB. Circ. cmt to surface. NU tree. Released rig on 1/16/80. WOCU.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Cooley Hatten TITLE Admin. Supervisor DATE

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE DATE

NM0001

*See Instructions on Reverse Side



ACCEPTED FOR RECORD

FEB 8 '80

DISTRICT

BY M. L. Kuchta