12-16-

Form Approved

## UNITED STATES

	Budget Bureau No. 42-R1424
5. LEASE	

DEPARTMENT OF THE INTERIOR	SF 078421
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
oo not use this form for proposals to drill or to deepen or plug back to a different servoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME McAdams
1. oil gas 区 other  2. NAME OF OPERATOR	9. WELL NO. 5E
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME Basin Dakota
3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-27-N, R-9-W
<ol> <li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li> </ol>	N.M.P.M.
AT SURFACE: 1830'S, 910'W AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE  San Juan New Mexico
AT TOTAL DEPTH:	San Juan New Mexico  14. API NO.
5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 FLEVATIONS (CLICW DE KDD AND WO)
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6364' GL
RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL JLL OR ALTER CASING ULTIPLE COMPLETE HANGE ZONES BANDON* Uther	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	It
<ul> <li>including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen</li> <li>Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cu</li> </ul>	irectionally drilled, give subsurface locations and to this work.)*  joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
<ul> <li>including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen</li> <li>Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cu surface. WOC 12 hours; held 600#/30 minutes.</li> </ul>	irectionally drilled, give subsurface locations and to this work.)*  joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
including estimated date of starting any proposed work. If well is discussived and true vertical depths for all markers and zones pertinents:  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cu surface. WOC 12 hours; held 600#/30 minutes.	irectionally drilled, give subsurface locations and to this work.)*  joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
including estimated date of starting any proposed work. If well is discussived and true vertical depths for all markers and zones pertinents:  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cusurface. WOC 12 hours; held 600#/30 minutes.  RECEIVED  DEC  DEC  U. S. GEOLOGICAL SURVEY.  FARMINGTON, N. M.	joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
including estimated date of starting any proposed work. If well is discussived and true vertical depths for all markers and zones pertinent.  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cusurface. WOC 12 hours; held 600#/30 minutes.  DEC  U. S. GEOLOGICAL SURVEY.  FARMINGTON, N. M.  Subsurface Safety Valve: Manu. and Type	joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
including estimated date of starting any proposed work. If well is discussived and true vertical depths for all markers and zones pertinents:  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cusurface. WOC 12 hours; held 600#/30 minutes.  PECEIVED  DEC  U. 8. GEOLOGICAL SURVEY.  FARMINGTON, N. M.  FARMINGTON, N. M.  B. I hereby certify that the foregoing is true and correct	joints 8 5/8", 24#, KS surface a.ft. cement. Circulated to
including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinenged:  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cusurface. WOC 12 hours; held 600#/30 minutes.  DEC  U. S. GEOLOGICAL SURVEY.  J. S. Hereby certify that the foregoing is true and correct	joints 8 5/8", 24#, KS surface of surface in the surface of surface in the surface of su
including estimated date of starting any proposed work. If well is displayed and true vertical depths for all markers and zones pertinents:  Spudded well. Drilled surface hole. Ran 5 casing 204' set at 218'. Cemented w/165 cusurface. WOC 12 hours; held 600#/30 minutes.  PECLIVED  DECLIVED  DECLIVED  DECLIVED  OURS GEOLOGICAL SURVEY.  FARMINGTON, N. M.  FARMINGTON, N. M.  FARMINGTON, N. M.  Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct of the principle of th	joints 8 5/8", 24#, KS surface of actions and to this work.)*  joints 8 5/8", 24#, KS surface of actions and the company of th

NMOCC'

\*See Instructions on Reverse Side

ACCEPTED FOR REGORD

DEC 1979

