UNITED STATES

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	1 Wolle		
Sun	dry Notices and Reports on Wells	11 13 17	
l. Type of Well GAS	DECEIVED MAR - 6 1995	5.	Lease Number SF-078421 If Indian, All. or Tribe Name
		7.	Unit Agreement Name
Name of Operator MERIDIAN OIL	OIL CON. DIV. Dist. 3	8.	Well Name & Number
3. Address & Phone No. o		0.	McAdams #5E
PO Box 4289, Farming	gton, NM 87499 (505) 326-9700	9.	API Well No. 30-045-23844
4. Location of Well, Foo	otage, Sec., T, R, M	10.	Field and Pool
1830'FSL, 910'FWL, Se	ec.20, T-27-N, R-9-W, NMPM	11.	Basin Dakota County and State
			San Juan Co, NM
Final Abandor	nment Altering Casing Co	nversion to	o Injection
13. Describe Proposed	or Completed Operations		
2-9-95 MIRU. ND	WH. NU BOP. SDON.		
2-10-95 TOOH w/2: pump 52 SDON.	18 jts 2 3/8" tbg. TIH to 6870'. Pum 2 sx Class "B cmt inside 4 1/2" csg	@ 6184-6870)'. POOH to 5284'. WO
2-13-95 TIH, tag 500 psi	cmt @ 5910'. POOH to 5798'. Load ho i, OK. Plug #2: pump 12 sx Class "B"	cmt inside	e csg @ 5643-5798'.
POOH to	o 3844'. Plug #3: pump 14 sx Class " o 2269'. Plug #4: pump 35 sx Class "	B" cmt ins: B" cmt @ 18	ide csg @ 3659-3844'. 307-2269'. POOH to 15
	o 7709.		
Plua #5	5: pump 23 sx Class "B" cmt inside c	sg @ 1208-:	1512'. TOOH. TIH, per
Plug #5 sqz hol 103 sx	5: pump 23 sx Class "B" cmt inside c les @ 268'. Establish circ out brade Class "B" cmt down csg and out brad	sg @ 1208-1 nhead w/10 lenhead. Ci	1512'. TOOH. TIH, per bbl wtr. Plug #6: pu rc 1 bbl cmt to surfa
Plug #5 sqz hol 103 sx ND BOP	5: pump 23 sx Class "B" cmt inside cles @ 268'. Establish circ out brade Class "B" cmt down csg and out brade. Cut off WH. Found cmt down 10' in	sg @ 1208-1 nhead w/10 lenhead. Ci: 4 1/2" csg	1512'. TOOH. TIH, per bbl wtr. Plug #6: pu rc 1 bbl cmt to surfa & down 2' in 4 1/2".
Plug #9 sqz hol 103 sx ND BOP 8 5/8"	5: pump 23 sx Class "B" cmt inside c les @ 268'. Establish circ out brade Class "B" cmt down csg and out brad	sg @ 1208-1 nhead w/10 lenhead. Ci: 4 1/2" csg	1512'. TOOH. TIH, per bbl wtr. Plug #6: pu rc 1 bbl cmt to surfa & down 2' in 4 1/2":
Plug #9 sqz hol 103 sx ND BOP 8 5/8"	5: pump 23 sx Class "B" cmt inside of les @ 268'. Establish circ out brade Class "B" cmt down csg and out brade. Cut off WH. Found cmt down 10' in annulus. Fill w/3 sx cmt. Install dlugged and abandoned 2-13-95. Approved as to plugging of the state of	enhead w/10 lenhead. Ci: 4 1/2" csg lry hole ma:	1512'. TOOH. TIH, per bbl wtr. Plug #6: pu rc 1 bbl cmt to surfa & down 2' in 4 1/2".
Plug #5 sqz hol 103 sx ND BOP 8 5/8" Well pl	5: pump 23 sx Class "B" cmt inside of les @ 268'. Establish circ out brade Class "B" cmt down csg and out brade . Cut off WH. Found cmt down 10' in annulus. Fill w/3 sx cmt. Install d lugged and abandoned 2-13-95.	esg @ 1208-: enhead w/10 lenhead. Ci: 4 1/2" csg lry hole ma. he well bore. ed until	1512'. TOOH. TIH, per bbl wtr. Plug #6: pu rc 1 bbl cmt to surfa & down 2' in 4 1/2"
Plug #5 sqz hol 103 sx ND BOP 8 5/8" Well pl	5: pump 23 sx Class "B" cmt inside of les @ 268'. Establish circ out brade Class "B" cmt down csg and out brade. Cut off WH. Found cmt down 10' in annulus. Fill w/3 sx cmt. Install dlugged and abandoned 2-13-95. Approved as to plugging of the Liability under bond is retain.	esg @ 1208-: enhead w/10 lenhead. Ci: 4 1/2" csg iry hole ma. he well bore. ed until	1512'. TOOH. TIH, per bbl wtr. Plug #6: purc 1 bbl cmt to surfa & down 2' in 4 1/2" rker w/17 sx cmt. RD.
Plug #5 sqz hol 103 sx ND BOP 8 5/8" Well pl	5: pump 23 sx Class "B" cmt inside of les @ 268'. Establish circ out brade Class "B" cmt down csg and out brade. Cut off WH. Found cmt down 10' in annulus. Fill w/3 sx cmt. Install dlugged and abandoned 2-13-95. Approved as to plugging of the Liability under bond is retained that the foregoint acceptance the stage of the complete that the foregoint acceptance the stage of the complete that the foregoint acceptance the stage of the complete that the foregoint acceptance the stage of the complete that the foregoint acceptance the stage of the complete that the foregoint acceptance the stage of the complete that the foregoint acceptance to the complete that the comple	esg @ 1208-: enhead w/10 lenhead. Ci: 4 1/2" csg iry hole ma. he well bore. ed until	1512'. TOOH. TIH, per bbl wtr. Plug #6: purc 1 bbl cmt to surfa & down 2' in 4 1/2" rker w/17 sx cmt. RD.

APPROVER

MAR 0 2 1995