

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800'S, 800'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 01074
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Huerfano Unit
8. FARM OR LEASE NAME  
Huerfano Unit
9. WELL NO.  
275
10. FIELD OR WILDCAT NAME  
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 36, T-27-N, R-11-W  
N.M.P.M.
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6489' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-29-80: Set speedy line 4 1/2" bridgeplug set at 6389'. Set RTTS packer at 6328'. Tested plug to 3500#, OK. Isolated casing leak between 5430' and 5490'. Set RTTS at 5175'. Cemented w/ 118 cu. ft. cement.

3-31-80: PBD 6775'. Tested casing to 4000#, OK. Perfed 6517, 6520, 6522, 6548, 6599, 6607, 6611, 6644, 6648, 6652, 6656, 6659, 6662, 6672' W/1 SPZ. Fraced w/124,000# 20/40 & 31,500 10/20 sand, 56,600 gal. wtr. Flushed w/2100 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED J. D. Drisco TITLE Drilling Clerk DATE April 8, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL: RECORDED FOR RECORD

APR 10 1980

\*See Instructions on Reverse Side

BY [Signature]

NMOCC

