

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other  
well well

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1085' FNL 1090' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Spudding/csg. report

5. LEASE

SF-078390

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Price Com

9. WELL NO.

#4

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 24, T28N, R8W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6219' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/23/80 - 8/31/80

Spudded 12 1/4" hole 8/22/80. Ran 7 jts. (285') of 9 5/8" 36# csg. Set @ 297'. Reduced hole to 8 3/4" drill to 3500'. RU and ran 87 jts. 7" 23# csg. Set @ 3499'. Cmt w/392 sx 65/35 Lite followed w/150 sx CL-B w/2% CACL2. Set slips. Reduced hole to 6 1/4" drilled to TD of 7385'. RU & ran 100 jts. of 4 1/2" 10.5/11.6# csg. Set @ 7324' w/TOL @ 3259'. Cmt. w/198 sx 65/35 POZ mix, 6% gel. 0.4 HR-4, 0.5% CFR2. Reverse out 11 bbls of cmt. Rig released @ 7:30 p.m., 8/31/80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carolyn V. Hutton TITLE Asst. Div. Adm. Mgr. DATE October 1, 1980

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

OCT 08 1980

FARMINGTON DISTRICT

BY BW

\*See Instructions on Reverse Side