91 Test

## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: M22/27/10

## OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	NAME RESE	RVOIR OR P	1	TYPE PROD METHO		THOD PR	PROD MEDIUM PROD			
PR OMP	GORDON JC	D 2E DK	94142	-						
VR OMP	GORDON JC	1				<u> </u>				
	<b>4</b> 8€ 16	PRI	E-FLOW	SHUT-IN P	RESSURE DA	TA	abe; a	; <u></u>		
	Hour/Date Shut-In		Length of Time Shu		Shut-In	SI Press. PS		PSIG	Stabilzed	
PR OMP	03/13/92		72 Hours			2			Yes	
VR OMP	02/13/92		72 Hours			•	546		No	
	.	<u></u>	!	FLOW TEST	DATE NO.1					
omme	enced at (ho	ur,date)*	<u></u>				Zone I	Produci	ng (Upr/Lw	
TIME LAPSED (hour, date) SINCE							Prod Temp.	REMARKS		
02/20/92 Da		Day	1	- 2 S				Bot	h Zones SI	
02/26/92		Day 2		2	546				h Zones SI	
0 <b>2/15</b> /92 Da		Day	3	2	546		,	Bot	h Zones SI	
02/3€/92 Day		Day	4	2 546				lowe	d lower	
02/1 <b>4</b> /92 Day		Day	5 1		405				d lower	
01/1/92 Day		6	2 405							
rodu	uction rate	BOPD	based MFCP	D:Tested th	neu (Orifi	.ce	or mete	Grar):METE	av GOR _	
		· · · · · · · · · · · · · · · · · · ·	MID-T	EST SHUT-IN	PRESSURE	DA	TA			
JPR COMP	Hour, Date	ngth of Time SI SI Pres		PEB2 5 1932						
LWR COMP								- 111 CC	)M. DIV. St. 3	

FLOW TEST NO. 2

mmenced at (hour, dat	(e) **		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRESSURE		PROD. ZONE			
(hour, date)	SINCE **	Upper Completion	Lewer Completion	TEMP.	REMA	NRKS	
	ļ						
<del></del>	<del> </del>					<del></del>	
			<b></b>			<del> </del>	
		1					
		ŀ					
duction rate d	_	D based on	Bbls. in	Hours.	Grav	GOR	
					):		
			ID. Itsky unu	(Office of Meter	);		
narks:	<del></del>			<del></del>	· · · · · · · · · · · · · · · · · · ·		
			·			<del></del>	
ereby certify th	at the informati	on herein contain	ed is true and co	mplete to the bes	t of my knowledge.	20	
proved	FEB 25 19	91		. /	1	had to	
New Mexico Oi	il Conservation I	Division	_ 19 (	Operator	moco o	vaucus	
	_		Е	ov //2+1	Inses &	ist	
Oriaina	of Signed by CHAR	LES GHOLSOU		~ 2	0. 22 10-	7. /	
	<u> </u>		T	Title	uld o	een	
le <u>DETUTY</u>	OIL & GAS INSPE	CTOR, DIST, #13	г	Date	2-21-92		
			A				

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Plow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereofe, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least revice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).