

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1520 FNL X 790 FEL  
AT SURFACE: Section 22, T27N, R10W  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) completion

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



5. LEASE  
SF-077952

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
J. C. Gordon "D"

9. WELL NO.  
1E

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M.; OR BLK. AND SURVEY OR AREA SE/4-NE/4  
Section 22, T27N, R10W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.  
30-045-24101

15. ELEVATIONS (SHOW DF, KDB AND WD)  
6249' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Completion operations commenced on 5-26-80. Total depth of the well is 6811', and plugback depth is 6763'. Perforated intervals from 6506'-6519', and 6596'-6638', with 2 SPF, a total of 120, .38" holes. Perforated intervals from 6679'-6682', and 6689'-6705', with 2 SPF, a total of 38, .38" holes. Sand-water fraced with 133,360 gal of frac fluid and 380,000# of 20-40 sand. Landed 2-3/8" tubing at 6713'. Swabbed the well and released the rig on 5-31-80.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

Signed By  
E. SVOBODA

TITLE Dist. Adm. Supvr. DATE 6-11-80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

DATE ACCEPTED FOR RECORD

JUN 18 1980

\*See Instructions on Reverse Side

BY [Signature]