UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9-331 Dec. 1973	Budget Bureau No. 42-R1424	
UNITED STATES	5. LEASE	
DEPARTMENT OF THE INTERIOR	SF-078872A	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
• 1	Frontier "E"	
1. oil gas \overline{X} other	9. WELL NO.	
2. NAME OF OPERATOR	1-E	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR P.O. Drawer 570, Farmington, New Mexico 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.)	Basin Dakota/Kutz Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 4, T27N, R11W	
AT SURFACE: 1865' FNL & 1520' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH	12. COUNTY OR PARISH 13. STATE San Juan New Mexico	
is probabilitation () in ski to line distanti in cital se homba.	14. API 110.	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6155' GR	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0100 011	
CHANGE ZONES -BANDON Perforation in Stimulation Rpt X Production Tubing Report X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state of the complete of the comple	rectionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertiner 11/28/80 Perforated the Dakota at 6556', 6562 6592', 6621', 6644'. Total of 9 hole Frac'd with 102,202 gals 30# gelled	2', 6568', 6574', 6579', 6586', s.	

measurea :	assimated that or starting any proposed work, it well is in ectionally dif- and true vertical depths for all markers and zones pertinent to this work.	irad. give subsurface locations and)*
11/28/80	Perforated the Dakota at 6556', 6562', 6568',	6574', 6579', 6586',
	6592', 6621', 6644'. Total of 9 holes.	
	Frac'd with 102,202 gals 30# gelled 1% KCl wa	ater and 58,300# 20/40 sar
	AIR 19.5 BPM, ATP 1200 psi, ISIP 750 psi.	
	Perforated the Gallup at 5812', 5820', 5828',	5833', 5838', 5843', 5848',
	5853', 5858', 5877', 5 886', 5920', 5925', 5984'	, 5990%, 5994'.
	Total of 16 holes.	ି କଳିକ୍ରିଆ ଓଡ଼ିଶ୍ୟର୍ଥି
11/29/80	Foam frac'd Gallup with 39,278 gals 2% KCl as	nd 1,145,945 scF Nitrogen
	and 72,000# 20/40 sand. AIR 30 BPM, ATP	2500 psi, ISIP 2300 psi.
11/30/80	Landed Model 'D" Packer on wireline at 6145'	. Ran 210 joints of
	2-3/8", 4.7#, J-55 landed in Model "D" packet	er at 6145', with tail pipe
	at 6641'. Landed 190 joints of 1-1/2", 2.90#,	, CSR tubing at 6002'.
	·	्रेंच्य स्टब्स्ट स्टब्स्ट के हैं। इ.स.च्या स्टब्स्ट के ब्रिक्ट स्टब्स्ट के ब्रिक्ट स्टब्स्ट स्टब्स्ट स्टब्स्ट स्टब्स्ट स्टब्स स्टब्स स्टब्स स्टब्स
Subsurface Saf	ifety Valve: Manu. and Type	Set @
		- 1933 and 1931
18. I hereby ce	ertify that the foregoing is true and correct	

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

TITLE Dist. Prod. Mgr. DATE December

(This space for Federal or State office use)

_ TITLE _