

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1850' FSL x 1115' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

5. LEASE
SF 077385A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Johnson Gas Com B

9. WELL NO.
IE

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
NE/4 SE/4, Section 21
T27N-R10W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.
30-045-24166

15. ELEVATIONS: (SHOW DEPTH AND WD)
6081 GL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Completion</u>	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 12-1-80. Total depth of the well is 6580' and plugback depth is 6535'. Perforated interval from 6446' to 6464' with 2 spf, a total of 36, .38" holes. Perforated intervals from 6295-6305', 6331-6337', 6382-6424', with 2 spf, a total of 116, .38" holes. Sandwater fraced with 145,000 gallons of frac fluid and 396,000 # of 20-40 sand. Landed the 2 3/8" tubing at 6483. Swabbed the well and released the rig on 12-8-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Dist. Admin. Supv DATE 1/19/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

BW