

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
DEPCO, Inc.
3. ADDRESS OF OPERATOR
1000 Petroleum Building--Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1070' FNL, 1070' FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Supplementary Report

5. LEASE
SF-078896
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--
7. UNIT AGREEMENT NAME
--
8. FARM OR LEASE NAME
Federal 32
9. WELL NO.
41
10. FIELD OR WILDCAT NAME
West Kutz P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 32-T27N-R11W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
30-045-24269
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6189' GR; 6201' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 11:30 AM 5-11-80. Drilled 12 1/4" hole to 140' KB. Ran 3 jts 8-5/8" 24# - K55 surface casing, landed @ 138' KB. Cemented w/100 sx Regular Class "B" containing 3% CaCl₂. Circulate cement to surface. WOC 12 hrs. Drilled to 1940' TD. Ran DIL and CNL-FDC w/GR logs. Set 4 1/2" - 10.5# - K55 casing @ 1940' KB. Cemented w/250 sx 50/50 pozmix containing 6% gel, 1/4# flocele/sx, 6 1/4# gilsonite/sx followed by 100 sx Regular Class "B". Rig released 5:00 AM 5-14-80.

Subsurface Safety Valve: Manu. and Type None Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. F. Schwenn Prod. Supt. DATE 5/14/80

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 28 1980

*See Instructions on Reverse Side

BY AK FARMINGTON DISTRICT