(June 1990) DEPARTMEN		TED STATES T OF THE INTERIOR AND MANAGEMENT	PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.	
		AND REPORTS ON WELLS	NOO-C-14-20-7467	
	6. If Indian, Allottee or Tribe Name			
Do not use this	Navajo			
	7. If Unit or CA, Agreement Designation			
I. Type of Well Gil Gi	a - Other		8. Well Name and No.	
2. Name of Operator				
•	Lucky Billy Charlie			
3. Address and Telephor	roduction Corp.		30-045-24330	
•	x 420, Farmington, N	M 07400 /E0E\ 22E 1021	10. Field and Pool, or Exploratory Area	
4. Location of Well (For	ouge, Sec., T., R., M., or Survey Des	M 87499 (505) 325–1821	WAW Fruitland Sand Po	
2000.000 01	mge, see., 1., K., M., or survey Des	(npion)	11. County or Parish, State	
	- 790' FWL		11. County of Parish, State	
Sec. 22,	T27N, R13W, NMPM		San Juan, NM	
12. CHECK	(APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE O	F SUBMISSION	TYPE OF ACTION	· · · · · · · · · · · · · · · · · · ·	
Notice	e of Intent	Abandonment	Change of Plans	
		Recompletion	New Construction	
∟ Subse	quent Report	Plugging Back	Non-Routine Fracturing	
		Casing Repair	Water Shut-Off	
☐ Final	Abandonment Notice	Altering Casing	Conversion to Injection	
		Other	Dispose Water (Note: Report results of myltiple completion on Well	
give subsurface k Plug	cations and measured and true vertical	ortinent details, and give pertinent dates, including estimated date of starting depths for all markers and zones pertinent to this work.) The class B with 6% gel down juli 0 1992 OIL CON. DIV DIST. 3 SEE ATTACHED FOR	n 2-7/8" Casing	
4. I hereby cartification it	foregoing is true and correct	CONDITIONS OF APPROVAL		
Signed	Olevandh	Title Operations mgt.	APPHUVED	
(This space for Federal		The Charles India	JUL 07 1992	
Approved by		Title	1002	
Conditions of approval,	if any:	NMOCD AKE	AREA MANAGER	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

- 8. Within 30 days after plugging work is completed, file a Sundry Notice (Subsequent Report of Abandonment, Form 3160-5), in quintuplicate with Area Manager, Bureau of Land Management, 1235 La Plata Highway, Farmington, NM 87401. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 9. All permanently abandoned wells are to be marked with a regulation marker (4" pipe extending 4' above the ground line) containing the information as specified in 43 CFR 3162.6(d). Unless otherwise approved.
- 10. After plugging work is completed the surface is to be rehabilitated in accord with instructions from the Fluids Surface Management Section of the Farmington Resource Area Office.

All above are minimum requirements. The period of liability under the bond of record will not be terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.

Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1.

You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

GENERAL REQUIREMENTS FOR PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES FARMINGTON RESOURCE AREA

- 1. Secure prior approval either on a Sundry Notice (Form 3160-5) or verbally from the Fluids Drilling & Production Section at this office before changing the approved plugging program.
- 2. Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs. The Operator is responsible for providing all measuring devices needed to assure proper measurement of materials being used.
- 3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations. Unattended pits are to be fenced.
- 4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 100 feet in length with 50% excess inside casing or 100% excess when plug is set in open hole or squeezed into perforations. 15.6#/gal slurry weight is to be used when using class B neat cement or when CaCl₂ is used. Use the recommended slurry weight of other type cements when they are used (Class C, Pozzolan etc.).
- 5. Any cement plugs placed when well is not full of fluid, or when well may be taking fluid, (i.e. across perfs-unless bridge plug or retainer is used, across bad csg., or fresh water formations) will be tagged (touched) after cement has set to verify proper location.
 - 5a. Testing The first plug below the surface plug shall generally be tested by either tagging the plug with the working pipe string, or pressuring to a minimum pump (surface) pressure of 1000 psig, with no more than a 10 percent drop during a 15-minute period (cased hole only). If the integrity of any other plug is questioned, it must be tested in the same manner. Also, any cement plug which is the only isolating medium for a fresh water interval or a zone containing a valuable mineral deposit should be tested by tagging with the drill string.
- 6. Mud must be placed between plugs. Plugging mud is to be made up with a minimum of 15 lbs/bbl of sodium bentonite, and a nonfermenting polymer.

 Minimum consistency of plugging mud must be 9 lbs/gal and with a minimum viscosity of 50 sec/qt. Fresh water is to be utilized for mixing mud.
- 7. Following the placement of a cement plug, the withdrawl rate for at least the length of the cement plug shall not exceed 30 ft/min, in order to minimize the contamination of the plug.

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA 1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 1 Lucky Billy Charlie

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."

2. Mark Kelly with the Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907

3. Blowout prevention equipment is required.

4. The following modifications to your plugging program are to be made (when applicable):

After the cement has set, tag top of cement and refill casing, if Necessary.

Form 3160-5 (June 1990)	UNITED STATES DEPARTMENT OF THE INTERIOR RECEIVED BUREAU OF LAND MANAGEMENT BLM		PORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
	BUREAU OF LAND MANAGI	5. Lease Designation and Serial No.	
SUNC	NOO-C-14-20-7467 6. If Indian, Allottoe or Tribe Name		
Do not use this form for Use "AP	eservoir. Navaio		
	7. If Unit or CA, Agreement Designation		
I. Type of Well Oil Well Well Oth	8. Well Name and No.		
2. Name of Operator	Lucky Billy Charlie 1		
Dugan Production	9. API Well No.		
3. Address and Telephone No.	30-045-24330		
P.O. Box 420, F	10. Field and Pool, or Exploratory Area WAW Fruitland Sand PC		
790' FSL - 790'	11. County or Parish, State		
Sec. 22, T27N,	San Juan, NM		
12. CHECK APPRO	PRIATE BOX(s) TO INDICATI	E NATURE OF NOTICE	, REPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION		ACTION	
Notice of Intent	[X]	Abandonment Recompletion	Change of Plans New Construction
Subsequent Report		Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment	Notice \square	Altering Casing Other	Conversion to Injection Dispose Water (Note. Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Plugged well as follows:

1. Establish rate 2 BPM @ 400 psi. Fill 2-7/8" casing with class "B" neat cement, 47 cu.ft.

2. Check cement top at 25'.

3. Fill top of casing with cement, set dry hole marker. complete 8-21-92.

> Approved as to plugging of the well back. Liability under bond is retained until surface restoration is cornelated.

SELECT TOTOLOGIST IN COMPACED.				
Signed 1000 Constitution of the second of th	Tide	Operations Manager	Date 8/28/92	
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title		APPROVED	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any table, floringus for produlent statements or representations as to any matter within its jurisdiction.

SEP 3 1002

OIL COM THE \Dist, a