

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other _____
 2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY
 3. ADDRESS OF OPERATOR
501 Airport Drive, Farmington, NM 87401
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
 AT SURFACE: 860' FSL X 1845' FEL
 AT TOP PROD. INTERVAL: Same
 AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud and set casing _____	

5. LEASE
SF 077329
 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
 7. UNIT AGREEMENT NAME
 8. FARM OR LEASE NAME
Martin Gas Com C
 9. WELL NO.
1E
 10. FIELD OR WILDCAT NAME
Basin Dakota
 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SW/4 SE/4 Section 11, T27N, R10W
 12. COUNTY OR PARISH
San Juan
 13. STATE
NM
 14. API NO.
30-045-24478
 15. ELEVATIONS (SHOW DF, KDB, AND WD)
6043' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 13-1/4" hole on 2-22-81 and drilled to 312'. Set 8-5/8" 24# surface casing at 311' on 2-22-81, and cemented with 350 sx of class "B" neat cement containing 2% CaCl2. Good cement was circulated to the surface. Drilled a 7-7/8" hole to a TD of 6600'. Set 5-1/2" 15.5# production casing at 6591', on 3-5-81, and cemented in two stages.
 1) Used 500 sx of class "B" neat cement containing 50/50 poz, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" neat cement.

2) Used 490 sx of class "B" neat cement containing 50/50 poz, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with
(over)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

Original Signed By
SIGNED E. E. SVOBCDA TITLE Dist Admin Supvr DATE 3/11/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

MAR 17 1981

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY [Signature]

ACCEPTED FOR RECORD

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

100 sx of class "B" neat cement. No cement was circulated to the surface. The DV tool was set at 3361'. The rig was released on 3-5-81.