

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with well state requirements)*

At surface 800' FSL & 1530' FEL

At top prod. interval reported below

At total depth

RECEIVED
MAY 26 1981
U.S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

14. PERMIT NO. _____ DATE ISSUED _____

5. LEASE DESIGNATION AND SERIAL NO.

SF-077384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanks

9. WELL NO.

14-E

10. FIELD AND POOL, OR WILDCAT

✓ Basin Dakota

Fulcher Kutz Pictured Cliffs

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Section 12, T27N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

15. DATE SPUDDED 11-20-80 16. DATE T.D. REACHED 12-03-80 17. DATE COMPL. (Ready to prod.) 4-6-81 18. ELEVATIONS (DF, REB, RT, GR, ETC.)* 6118' GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 6690' 21. PLUG, BACK T.D., MD & TVD 6646' 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 0-6690 ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

6430'-6622' (Dakota)

25. WAS DIRECTIONAL SURVEY MADE

Deviation

26. TYPE ELECTRIC AND OTHER LOGS RUN

IES, GR-Density, GR-Collar and GR-CBL Logs

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	222'	12-1/4"	140 sacks	
5-1/2"	15.5#	6690'	7-7/8"	775 sacks (3 stages)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
---	---	---	---	---	1-1/2"	6620'	2209'

31. PERFORATION RECORD (Interval, size and number)

Dakota: 6430', 6436', 6474', 6521', 6526',
6531', 6536', 6541', 6546', 6584',
6600', 6610', 6622'. (13 holes)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6430'-6622'	Frac'd with 110,500 gals 30# gelled 1% KCl water and 77,000# 20/40 sand.

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
		Flowing				Shut-In	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
5-5-81	3	3/4"	→				
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
45	---	→		657			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold

TEST WITNESSED BY

Steve Kellenagers

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

TITLE District Production Manager

DATE

MAY 27 1981

May 20, 1981

FARMINGTON DISTRICT

*(See Instructions and Spaces for Additional Data on Reverse Side)

BY

KBS

NMOCC

ACCEPTED FOR RECORD

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	NAME	TOP	
				MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	1222'				
Fruitland	1798'				
Pictured Cliffs	2017'				
Chacra	2930'				
Cliff House	3582'				
Point Lookout	4340'				
Gallup	5533'				
Greenhorn	6331'				
Graneros	6392'				
Dakota	6512'				