

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well2. NAME OF OPERATOR
Ladd Petroleum Corporation3. ADDRESS OF OPERATOR
830 Denver Club Bldg. Denver, Colo. 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1000' FSL, 640' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) Casing report and spudding ☐5. LEASE
NM 027

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Knauff9. WELL NO.
1-E10. FIELD OR WILDCAT NAME
Basin Dakota11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13-T-27N-R-10W12. COUNTY OR PARISH
San Juan13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6494 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well was spudded on 12-18-80 by Westwind Drllg. Co. Surface casing: Ran 8 jts 8 5/8" 24# K-55 casing. Set @ 270'. Cemented w/275 sx Class "B" + 2% CaCl₂ cement. Circulated. Date: 12/19/80.

Prod. Csg: Ran 172 jts 4 1/2" 10.5# K-55 csg. Set @ 7050'. DV. Tools @ 5295' and 2972'. Cement 1st stage w/300 sx Dowell lite + 100 sx Class "B". Cement 2nd stage w/465 sx Dowell lite + 100 sx Class "B". Cmt 3th stage w/500 sx Dowell lite + 500 sx Class "B". No returns on 1st & second stages. Returns on third stage, cement circulated. Date: 1/1/81.

Subsurface Safety Valve: Manu. and Type N/A Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. M. TITLE Drilling Engineer DATE April 21, 1981

(This space for Federal or State office use)

APPROVED BY TITLE DATE ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL IF ANY

APR 24 1981

FARMINGTON DISTRICT
BY