

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Petroleum Energy

3. ADDRESS OF OPERATOR

P. O. Box 2121, Durango, Colorado 81301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' from South line & 660' from West

AT SURFACE: Line

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

SEP 08 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 8 1/4" hole to 2745'. Drilled 6 1/4" hole to 3550'. Ran 3557' 4 1/2" 10.5 ERW casing, set at 3550'. Cemented with 275 sks Howco Lite cement, tailed in with 100 sks class B cement. Plug down at 7:45 A.M., 8/12/80. Drilled 3 7/8" hole to 3675'. Good flow of gas at 3655'. Set tubing at 3525'. Hooked up well head. Well completed 8/16/80.



Subsurface Safety Valve: Manu. and Type

Set @

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE AGENT DATE 9/5/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 12 1980

FARMINGTON DISTRICT

BY [Signature]

\*See Instructions on Reverse Side

NMOCC