

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Northwest Pipeline Corporation
3. ADDRESS OF OPERATOR
P.O. Box 90, Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1250' FEL
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Commence Drlg operations		

5. LEASE
I-149-IND-8465
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Blanco
9. WELL NO.
#2A
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA
Sec 12 T27N R9W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-045-24526
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5934, CR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Feb 3, 1981 Spudded 13-3/4" surface hole at 2100 hrs 2-3-81.

Feb 4, 1981 Ran 5 jts (199') of 9-5/8", 36#, K-55, ST&C & set at 212'. Cemented w/ 120 sx Cl "B" w/ 1/4# flovele/sx & 3% CaCl₂. Displaced plug w/ 15 bbls wtr & down & 0715 hrs 2-4-81. Circ out 1 bbl² cmt.

Feb 5, to Feb 6, 1981 Drlg ahead with wtr.

Feb 7, 1981 Ran 59 jts (2303') of 7", 20#, K-55, ST&C & set at 2315'. Cemented w/ 100 sx 65/35 poz w/ 12% gel. Tailed w/ 100 sx Cl "B" w/ 2% CaCl₂. Plug down @ 0730 hrs 2-7-81. Dried hole up to drill ahead.

Feb 8, to Feb 9, 1981 Drlg ahead w/ gas.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ F.:

18. I hereby certify that the foregoing is true and correct

SIGNED Donna J. Brace TITLE Production Clerk DATE Feb 12, 1981

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FEB 19 1981

FARMINGTON DISTRICT

BY BW

*See Instructions on Reverse Side