

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

REPORT ON COMPLETION OF
(Include Production Data)
Form 7-81

Form 7-81
Include Production Data
Form 7-81

SE-078094

SUMMARY FACTS AND RESULTS ON WELLS

(Do not use this form for proposals to drill or to change or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. NAME OF OPERATOR
Gulf Oil Corporation

2. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 87400

3. LOCATION OF WELL (Report location clearly and in accordance with Key State Requirements.
See also space 17 below.)

990' FWL & 990' FWL

4. NAME OF WELL (Report location clearly and in accordance with Key State Requirements.
See also space 17 below.)

5. SURFACE

990' FWL & 990' FWL

6. DEPTH OF WELL

7. DEPTH OF WELL (ONLY IF DIFFERENT FROM 6.)

6064' GL

8. NAME OF WELL

Fullerton Federal

9. WELL NO.

12

10. FIELD AND POOL, IF KNOWN

W. Kutz Pictured Cliffs

11. SEC. T. R. S. OF LAND
SURVEY OR PLAN

Sec 11-T27N-R11W

12. COUNTY OF FIELD

San Juan

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF ABANDONMENT

SUBSEQUENT REPORT OF:

1. WATER SHUT-OFF

2. FUEL OR ALTER CASING

3. WATER SHUT-OFF

4. REPAIRING WELL

5. FRACTURE TREATMENT

6. MULTIPLE COMPLETION

7. FRACTURE TREATMENT

8. ALTERING CASING

9. STOPPING OR ACIDIZING

10. ABANDONING

11. STOPPING OR ACIDIZING

12. ABANDONING

13. OTHER WELL

14. CHANGING DEPTH

(Other) Casing

15. OTHER WELL

(Other)

(Note: Report results of multiple completion or Well Completion or Recombination Report and Log, Form 7-81)

16. SUMMARY OF WELL (Report location clearly and in accordance with Key State Requirements.
See also space 17 below.)

TD 8A.M., 10-18-80; complete logs 12:30 A.M., 10-19-80. RU & ran 68 joints & 1 cut joint 2-7/8" J-55 6.5# 8RD WUE (2098') set at 2100'. Attempted to cement & tubing was plugged. Uplog tubing & pump 200 sacks cement (PT broke down); pump cement out. Cement with 200 sacks 65-35 poz mix & 175 sacks Class "B" 5% D-6. Plug down 9 A.M., 10-20-80. Circulate cement. WOC 18 hours. Test casing 5000#, ok.

ILLEGIBLE



ACCEPTED FOR RECORD

DEC 12 1980

Area Drilling Superintendent, DATE 12-11-80

APPROVED BY FARMINGTON DISTRICT

NMCCC