

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249 Englewood, Colorado 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FSL, 1520' FWL "O"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☒
☐
☐
☐
☐
☐
☐
☐

(other) Commence drilling operations

5. LEASE
SF-078480

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Dawson Federal

9. WELL NO.
#1M

10. FIELD OR WILDCAT NAME
Basin Dakota/Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 26 T27N R8W

12. COUNTY OR PARISH 13. STATE
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6712' gr

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/14/81 MIRURT. Spud well 3/13/81. Drill 12 1/4" hole to 340'. Circ and cond. hole TOOH Rig up and run 8 jts (323') of 9-5/8" 36# csg set @ 328'. Cmt w/225sx class-B w/ 2% CaCl₂. Circ cmt to surface. Plug down.
3/15/81 NUBOPS. Pressure test rams to 1000 PSI for 30 mins OK. Resume drilling.
3/23/81. Drill to TD @ 5500'. Start trip. Circ and cond. hole. RU and run logs. Circ to run 7" csg.
3/24/81. RU and run 126 jts (5487') 7" 23# csg set @ 5493' w/DV @ 3017'. Cmt w/ 300sx B-J Lite, Tail in w/150sx Class-B w/2% CaCl₂. Open DV and circulate 4 hours. WOC. Cmt 2nd stg. w/400sx B-J Lite tailed in w/150sx Class-B. Plug down. Set slips cut off csg. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carolyn M. Patton TITLE Asst.Div.Adm.Mgr. DATE March 25, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

APR 07 1981

FARMINGTON DISTRICT

BY Carolyn M. Patton

