

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other
well well
2. NAME OF OPERATOR
DEPCO, Inc.
3. ADDRESS OF OPERATOR
1000 Petroleum Bldg -- Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1630' FEL, 1825' FSL (NW/4 SE/4)
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) Subsequent Report of Operations

5. LEASE
SF-078896
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--
7. UNIT AGREEMENT NAME
--
8. FARM OR LEASE NAME
Federal 29
9. WELL NO.
33
10. FIELD OR WILDCAT NAME
West Kutz P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR
9-Area
Sec. 29-T27N-R11W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
30-045-24792
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6242' GR 6254' KB

(NOTE: Report results of multiple completion or zone change on Form 9-339.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 1:10 PM 3-26-81. Drilled 12 1/4" hole to 145' KB. Ran 3 jts - 130.32' - 8-5-8" 24# - K55 - R3 - ST&C casing landed @ 142' KB. Cmt'd w/100 sx Class "B" regular containing 3% CaCl₂ and 1 sx Flocele. Cmt circulated to surface. PD 5:30 PM 3-26-81. WOC 12 hrs. Drilled 7-7/8" hole to 2003' TD. Ran DIL and CNL/FDC and Caliper logs. Ran 48 jts - 1970.39' - 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1982' KB. Cmt'd w/275 sx 65/35 Pozmix, 12% gel, 12 1/4# Gilsonite/sx followed by 100 sx Class "B" regular. Good returns thru out. Cement circulated to surface. PD 10:15 PM. Rig released 11 PM 3-28-81. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Prod. Spt. - So. Rk DATE 3/31/81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

NMOCC