

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
DEPCO, Inc.

3. ADDRESS OF OPERATOR  
1000 Petroleum Bldg - Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FNL, 1840' FWL (NE/4 NW/4)  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Subsequent Report of Operations

5. LEASE

SF-078896

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 32

9. WELL NO.  
21

10. FIELD OR WILDCAT NAME  
West Kutz P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 32-T27N-R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

30-045-24793

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6148' GR 6160' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 2 PM 3-20-81. Drilled 12 1/4" hole to 145' KB. Ran 3 jts, 130.93' - 8-5/8" 24#, K55, R3, ST&C casing landed @ 142' KB. Cemented w/110 sx Class "B" regular containing 3% CaCl2 and one sx Flocele. Cement circulated to surface. PD 9:45 PM. WOC 12 hrs. Drill 7-7/8" hole to 1875' TD. Ran DIL and CNL/FDC w/GR-Caliper logs. Ran 45 jts, 1847.69' - 4 1/4", 10.5#, K55, R3, ST&C casing landed @ 1859' KB. Cemented w/275 sx 65/35 pozmix, 12% gel, followed by 100 sx Class "B" regular. Good returns thru out. Cement circulated to surface. PD 11:20 PM 3-22-81. Rig released 1 AM 3-23-81. WOC.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Prod. Spt. So. Rks DATE March 23, 1981

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

NMOCC

MAR 26 1981