UNITE	) STATES	5. LEASE
DFPARTMENT	OF THE INTERIOR	SF-078896
	CAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
020200		
SUNDRY NOTICES A	ID REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to	irill or to deepen or plug back to a different	
reservoir. Use Form 9–331–C for such p	oposals.)	8. FARM OR LEASE NAME
1. oil gas 🖄		Federal 33
well well en of	ier	9. WELL NO.
2. NAME OF OPERATOR		31
DEPCO, Inc.		10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR		West Kutz
1000 Petroleum Bldg	- Denver, CO 80202	11. SEC., T., R., M., OR BLK. AND SURVEY OF
	Γ LOCATION CLEARLY. See space 17	AREA
below.)		Sec. 33-T27N-R11W
AT TOP PROD. INTERVAL:	1850' FEL (NW/4 NE/4)	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Same	San Juan NM
	Same	14. API NO.
REPORT, OR OTHER DATA	TO INDICATE NATURE OF NOTICE,	30-045-24794
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:	6271' GR 6283' KB
TEST WATER SHUT-OFF		The state of the s
FRACTURE TREAT		
SHOOT OR ACIDIZE		
REPAIR WELL		(NOTE: Report results of multiple completed or zone change on Form (1) 230 2
PULL OR ALTER CASING		change on Form 91330 2 4
MULTIPLE COMPLETE	무슨 사람들은 바다 가장 하는 사람들이 되었다.	QIE CON. COM-
ABANDON*	H	DIST. 3
(other) Subsequent Repo	t of Operations	
including estimated date of	DMPLETED OPERATIONS (Clearly stat tarting any proposed work. If well is d pths for all markers and zones pertiner	e all pertinent details, and give pertinent dates irectionally drilled, give subsurface locations and to this work )*
	•	
opuomea 1 PM 4-11-81.	rilled 12%" hole to 155'	KB. Ran 3 jts - 135.14' - 8-5/8
44# - KDD - R3 - ST&C c.	sing landed @ 148' KB. C	emented w/225 sx Class "B" regul
containing 3% CaCl <sub>2</sub> and	one sx Flocele. Cement c	irculated to surface. PD 4:30 P
4-11-81. WOC 12 hrs.		The state of the s
Dui 11 - 1 - 7 - 7 / 0 H 1 - 1 - 1 - 1		
Jrilled /-//8" hole to	980' TD. Ran DIL and CNL	/FDC w/GR & Caliner logs Pan 4

Drilled 7-7/8" hole to 980' TD. Ran DIL and CNL/FDC w/GR & Caliper logs. Ran 48 jts - 1965.45' -  $4\frac{1}{2}$ " - 0.5# - J55 - R3 - ST&C casing landed @ 1977' KB. Cmtd w/265 sx 65/35 pozmix, 12% ge ,  $12\frac{1}{2}$ # gilsonite/sx followed by 100 sx Class "B" regular. Cement circulated to surface. PD 3:15 AM. Rig released 4 AM 4-14-81. WCC.

Subsurface Safety Valve: Manu. a d Type		Set @ Ft.
18. I hereby certify that the foreg jos	s is true and correct	
SIGNED ON W 3. EX	wkute Prod. Supt-So. Rockie	DATE 4/15/81
	(This space for Federal or State office use)	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	ACCEPTED FOR RECORD
		APR 2 1 1981
	*Saa Instructions on Payersa Sida	FARMINGTON DISTRICT

NMOCC