

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

Getty Oil Company

P.O. Box 3360, Casper, Wyoming 82602

below.)
 AT SURFACE: 1520' FNL & 790' FWL
 AT TOP PROD. INTERVAL: same
 AT TOTAL DEPTH: same

SUBSEQUENT REPORT OF:

(other)

ABANDON* ☐ ☐ ☐
(other) Date started and surface casing report and production casing report.

Date Spudded 2-22-81 4:30 PM

Ran 8 5/8" casing 2-22-81, set at 321' with 300 sks cement (circ. to top)

Ran 5 1/2" 14 & 15.5# casing 3-10-81, set at 6368' with 1360 sks cement

(Cement circulated on each of the 3 DV stages of cementing).

Cement circulated to surface on 8 5/8" casing and 5 1/2" casing.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles E. Mowry TITLE Area Engineer DATE 3-6-81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

• See Instructions on Reverse Side

MAR 26 1981

NMOCC

8