UNITED STATES

	1 3 LEADE .
DEPARTMENT OF THE INTERIOR	NOO-C-14-20-4158
GEOLOGICAL SURVEY	6./IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	Navajo 7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331—C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	none 9. WELL NO.
2. NAME OF OPERATOR	Navajo 2-32
PETROLEUM ENERGY, INC.	10. FIELD OR WILDCAT NAME
3. ADDRESS CF OPERATOR	Beautiful Mountain-Barker Creek
P.O.Box 2121 Durango, Co 81301	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Section 32
below.)1050' from North Line and 1610'	T 27N-R 19W, N.M.P.M.
AT SURFACE: from East Line, Sec 32,27N-19	M2. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: same as above	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
METORY, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5824 (GR)
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330)
MULTIPLE COMPLETE	
ABANDON*	
(other)	RESIDENCE DE L'ANDRE D
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinen 	irectionally drilled, give subsurface locations and
Due to unstable helium market, reques	t a change of zones to make
this well a Barker Creek completion (5590' to 5600'). Permission
to complete in Mississippian zone wil	l be requested if the market
for helium improves.	

Subsurface Safety Valves Manu. and Type _ Set @ .____ Ft. 18. I hereby certify that the foregoing is true and correct PETROLEAM ENE DATE March 17, 1982 agent Magness (This space for Federal or State office use) APPROVED BY ___ TITLE _ CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

AM000

FOT DISTAICT ENGINEER