UNITED	STATE	S
DEPARTMENT OF	THE	INTERIOR
GEOLOGICA	L SUF	RVEY

DEPARTMENT OF THE INTERIOR /	NOO-C-14-20-4158
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	NAVAJO
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different	
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil G gas C	· · · · · · · · · · · · · · · · · · ·
well well other	9. WELL NO.
2. NAME OF OPERATOR	NAVAJO 2-32
PETROLEUM ENERGY, INC.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	BEAUTIFUL MOUNTAIN
P. O. BOX 2121 DURANGO, COLORADO	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA SEC. 32, T27N, R19W
below.) 1050' FROM NORTH LINE AND	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	SAN JUAN . NEW MEXICO
AT TOTAL DEPTH: SAME	14. API NO. \
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	1
REPORT, OF OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	1.0
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SUBSEQUENT REPORT OF:	1 -
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE SEP 271 REPAIR WELL SEP 271	
SHOOT OR ACIDIZE SEP 21	MANIGE ARESON Atts of multiple completion or and
PULL OR ALTER CASING	OUR change in form 9=330.)
MULTIPLE COMPLETE	SEP 2 9 1983
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* MULTIPLE TREAT SEP 2.71 SEP 2.71	OH CON DIV
(other) COMPLETE	DIST. 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat	e all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	irectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertited	ic to this world,
	•
REQUEST PERMISSION TO COMPLETE IN THE	MISSISSIPPIAN FORMATION
4	a the second of the second
PERFORATE: 5856' to 5864'	- 1 . Detin
5872' to 5874' The la	uling and of cosing in it it
5887' to 5896' Mlas	unid and recorded at entered
5925' to 5941' of 15	laus or less.
7.3	whing and 5% coming in to be covered and recorded at interval a days or less.
TREAT WITH 5000 GALLONS 28% ACID	•
PLAN TO SET PACKER (UNI VI) AT 5800'	la dell'all'allanel
PLAN TO SET PACKER (UNI VI) AT 5800' Remporary abandonment of the R until forward & C, (984. Subsurface Safety Valve: Manu. and Type	porker inell is applied in
Subsurface Safely Velve: Manu. and Type	Set @ Ft.

TITLE AGENT

frue and correct

APPROVED

DATE SEPTEMBER 26, 1983

AS AMENDED :

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Peverse Side

MMOCF