

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
DEPCO, Inc.  
3. ADDRESS OF OPERATOR  
1000 Petroleum Bldg - Denver, CO 80202  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FSL, 1055' FEL (SE/4 SE/4)  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Subsequent Report of Operations	

5. LEASE  
--  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
--  
7. UNIT AGREEMENT NAME  
--  
8. FARM OR LEASE NAME  
Federal 32  
9. WELL NO.  
44  
10. FIELD OR WILDCAT NAME  
West Kutz P.C.  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 32-T27N-R11W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
NM  
14. API NO.  
30-045-24966  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6168' GR 6180' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 9 PM 4-14-81. Drilled 12 1/4" hole to 155' KB. Ran 3 jts - 134.11' - 8-5/8" 24# - K55 - R3 - ST&C casing landed @ 146' KB. Cemented w/100 sx Class "B" regular containing 3% CaCl<sub>2</sub> & one sx Flocele. Cmt circd to surface. PD 12:30 AM 4-15-81. WOC 12 hrs.

Drilled 7-7/8" hole to 1870' TD. Ran DIL & CNL/FDC w/GR & Caliper logs. Ran 45 jts - 1845.20' - 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1857' KB. Cemented w/250 sx 65/35 Pozmix, 12% gel, 12 1/2# gilsonite/sx followed by 100 sx Class "B" regular. Cement circd to surface. PD 5 AM. Rig released 5:30 AM 4-17-81. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John S. Schwenn Prod. Supt. - So. DATE 4/20/81  
Rockies

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 24 1981

\*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY John S. Schwenn