

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or deepen or plug back to different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

1000 Petroleum Building

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL, 1055' FEL (SE/4 SE/4)

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Subsequent Operations

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

RECEIVED

APR 27 1984

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

SF078896

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Federal 32

9. WELL NO.

44

10. FIELD OR WILDCAT NAME

W. Kutz P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 32-T27N-R11W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.

30-045-24966

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6168' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-23-84 MIRU Aztec Service Unit #204. POH & LD 49 jts - 1" tbq. PU & RIH w/2-7/8" tbq to 1668' PBD. P&A inside 4 1/2" - 10.5# prod csg as follows:

15 sx Cl "B" Reg cmt - 1668' to 1434' - Pictured Cliffs Form.

Tagged plug after 15" WOC period.

25 sx Cl "B" Reg cmt - 750' to 415' - Ojo Alamo Form.

10 sx Cl "B" Reg cmt - 196' to 96' - Opp. btm surf csg
(Set Bridge @ 68')

5 sx Cl "B" Reg cmt - 68' to surf - Top surf csg

Weldplate over 4 1/2" prod csg & 8-5/8" surf csg.

Erect dry hole marker.

RD & release rig.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. S. Schwert Prod. Supt. - So. DATE April 25, 1984
Rockies

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA

BY SA

MAY 01 1984