

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078499A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR  
LIVELY EXPLORATION COMPANY

3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod. Corp.  
P. O. Box 254 Farmington, N.M. 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1060'FNL, 1780'FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether on RT, or, etc.)  
6423'GL, 6436'DE, 6437'KB

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LIVELY

WELL NO.

11-E

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 16-T28N-R8W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

9/4/81 Spud Well

9/5/81 T.D. 270' Ran 6 joints 9-5/8", 36.0 lb. K-55 casing (252.95')  
set at 267' with 275 sacks Class "B" cement with 3% Calcium  
chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure  
test with 500 psig. Test ok.

9/8/81 T.D. 3345'. Ran 85 joints 7", 23.0 lb., K-55 casing (3350') set  
at 3345' with 400 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs.  
Gilsonite per sack followed by 200 sacks Class "B" cement with 2%  
Calcium Chloride.

10/19/81 T.D. 7251'. Ran 172 joints 4-1/2", 10.50 & 11.60 lb., J-55  
(7235') set at 7235' with 120 sacks 50-50 Pozmix (12% Gel) and  
6-1/4 lbs. Gilsonite followed by 80 sacks 50-50 Pozmix (2% Gel)  
with 6-1/4 lbs. Gilsonite and 6 lbs. Salt per sack.

Second Stage: 100 sacks 65-35 Pozmix with 6-1/4 lbs. Gilsonite  
per sack followed by 50 sacks Class "B" cement. Stage Tool at 4300'  
Temperature Survey - 2800' top of cement.

FOR: LIVELY EXPLORATION COMPANY

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY

SIGNED

Ewell N. Walsh P.E.

TITLE

President, Walsh Engr.  
& Production Corp.

DATE 10/21/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

NMOC