

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well ☐ well ☐
2. NAME OF OPERATOR  
Energy Reserves Group, Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 3280 - Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1,020' FSL & 790' FWL (SW/SW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO:      SUBSEQUENT REPORT OF:
- TEST WATER SHUT-OFF ☐ ☒
- FRACTURE TREAT ☐ ☐
- SHOOT OR ACIDIZE ☐ ☐
- REPAIR WELL ☐ ☐
- PULL OR ALTER CASING ☐ ☐
- MULTIPLE COMPLETE ☐ ☐
- CHANGE ZONES ☐ ☐
- ABANDON\* ☐ ☐
- (other) Well History ☐ ☒

5. LEASE SF-078019	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME E.H. Pipkin	
9. WELL NO. 18	
10. FIELD OR WILDCAT NAME Kutz Fruitland & West Kutz PC	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12-T27N-R11W	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) G.L. 6,001'; K.B. 6,006'	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above reference well was spudded @ 2:00 PM 9-26-81.

Drld 9-7/8" hole to 106'. Ran 3 jts 7" O.D., 23#, K-55, R-3, ST&C new casing set @ 105' (K.B.). Cemented w/60 sx of Class "B" cement w/2% CaCl<sub>2</sub> & 1/4# Flocele/sx. Plug down @ 6:00 PM 9-26-81.

Drld 6-1/4" hole to 1,936' and ran logs.

Ran 47 jts 4-1/2" O.D.. K-55, R-3, ST&C new casing set @ 1,910' (K.B.). Cemented w/400 sx of 50-50 Pozmix w/2% Gel; 0.5% CFR-2 & 1/4# Flocele/sx. Plug down @ 3:45 PM 10-1-81. Good cement returns.

10-02-81 - W.O.C.T.


Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Ramon C. Gilligan TITLE Drlg Supt.-RMD DATE 10-2-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:



RECEIVED FOR RECORD

*Handwritten signature: Dean Whitt*