

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

COPY

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS		5. LEASE DESIGNATION AND SERIAL NO.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals		NM 04202
SUBMIT IN TRIPLICATE		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. TYPE OF WELL OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. IF UNIT OR CA, AGREEMENT DESIGNATION Jackson
2. NAME OF OPERATOR CONOCO INC.		8. WELL NAME AND NO. Jackson #3
3. ADDRESS AND TELEPHONE NO. 10 Desta Drive, Suite. 100W Midland, Texas 79705-4500 (915) 686-5424		9. API WELL NO. 30-045-25315
4. LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 1430' FSL & 1140' FEL, UNIT LETTER "I", Sec. 10, T28N-R09W		10. FIELD AND POOL, OR EXPLORATORY AREA Blanco Mesa Verde
		11. COUNTY OR PARISH, STATE San Juan County
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION		TYPE OF ACTION
<input type="checkbox"/> Notice of Intent <input checked="" type="checkbox"/> Subsequent Report <input type="checkbox"/> Final Abandonment Notice		<input type="checkbox"/> Abandonment <input type="checkbox"/> Recompletion <input type="checkbox"/> Plugging Back <input type="checkbox"/> Casing Repair <input type="checkbox"/> Altering Casing <input checked="" type="checkbox"/> Other: <u>Squeeze Rpt.</u> <input type="checkbox"/> Change of Plans <input type="checkbox"/> New Construction <input type="checkbox"/> Non-Routine Fracturing <input type="checkbox"/> Water Shut-Off <input type="checkbox"/> Conversion to Injection <input type="checkbox"/> Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)		
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		
1/7/99 Check well 0#. TIH w/ 7" Halliburton pkr & bridge plug, set bridge plug @ 3800'. TOO H w/ pkr to 2400'. Pressure test csg. To 1500#. Held ok. TOO H w/ pkr & latch on to bridge plug. TOO H w/ bridge plug & pkr. LD bridge plug, TIH w/ pkr , set pkr @ 3777'. RU BJ, pump down tbg. to get rate, TOO H w/ pkr. Note: 10:18 am called Earl Beecher w/ BLM, left message informing him of the casing leak and what we planned to do. At 1:50 pm called BLM again and left message to inform them that we would not be cementing until in the morning.		
1/8/99 TIH w/7" Hbton cement RET on 2 3/8" set @3771' test tbg in retainer test position to 1500# OK, sting into ret, RU BJ, pump 16 bbls fresh H2O @ 3 BPM to clear tubg & insure pumping into retainer, lead in w/175 sxs(210 cuft) Class H cement w/fluid loss additive (FL 52) & 1% CACL @ 2.5 BPM Max 250#, displaced w/13.5 bbls fresh H2O, squeezed to 300#, hesitated 15 min, pressure @ 250#, stung out of retainer, left 1.5 bbls cmt on top of retainer (approx 40' of cmt), RD BJ, TOO H w/2 3/8" tbg. will drill out cmt & test on Monday Jan 11th.		
1/11/99 TIH w/ 6 1/4" bit & 3 1/8" drill collars, tag cmt @ 3622'. PU swivel, start drilling on cmt. Hit stringers to top of cmt retainer @ 3741'. DO cmt ret., then drilled out cmt to 3844'. Run 5 bbl sweep. Blow dry. Pulled up off cmt.		
14. I hereby certify that the foregoing is true and correct		
SIGNED <u>Verla Johnson</u> (This space for Federal or State office use)		TITLE <u>VERLA JOHNSON, As Agent for Conoco Inc.</u> DATE <u>1-27-99</u>
APPROVED BY _____ Conditions of approval, if any:		TITLE _____ DATE <u>FEB 11 1999</u>
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unites States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.		

* See Instruction on Reverse Side

NMOCD