工9279

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: I092709 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

l	NAME KESE	RVOIR OR I	POOL		TYPE PROD	METHOD PRO	M D	EDIUM PROD	
PR OM:P	RIDDLE COM	A 001M M	V 9462	?5	GAS	FLOW		TBG	
TR OM:P	RIDDLE COM	A OOLM D	K 9462	23	GAS FLOW		TBG		
		PRI	E-FLOW	SHUT-IN P	RESSURE DA	.TA			
	Hour/Date	: Shut-In	Leng	yth of Time	Shut-In	SI Press.	PSIG	Stabilzed	
R MP	10/16/91			72 Hours		@-		No	
R MP	10/16/91			72 Hours		210		yes	
	I		l	FLOW TEST	DATE NO.1	-		1 9	
mmer	nced at (ho	our,date)*				Zone Pr	oduci	ng (Upr(Lw	
(hou	TIME LAPSEI (hour, date) SING				SSURE Lower	Prod Temp.	1 254		
10	0/16/91	Day 1		22	210		Botl	h Zones SI	
1(0/17/91	Day :	2	22	216		Botl	h Zones SI	
1(0/18/91	Day :	3	10	210		Boti	h Zones SI	
10/19/91		Day	4	0	210		llon	ree lower	
10/20/91		Day	5	0	179	<i> </i> /	f -2	u comer	
10/21/91		Day	6	9	174			it	
oduo	ction rate	BOPD 1	based MFCPI	on B D:Tested th	eu (Orific	Hrs ce or Meter) DATA	Gra	v GOR _ R	
PR MP	Hour, Date	e SI Len	gth oi	f Time SI	SI Press.		abiliz	ed (yes/no	
	I							<u> </u>	

Commenced at flour, date	in a second		TEUW IEST	Zone producing (Upp	or or Lawerk
THIS THE	LAPSED TIME	entities Completes &		PROD. ZOME TEMP.	REMARKS
X 199		1-4	DEST: AT 10	-	The state of the s
-	÷				e.
					Grav GOR
Remarks:				(Ortrice or Meter)	:
Approved New Mexico Oil	DEC 3 0 1 Conservation Di	991 vision	_ 19 O	perator	moco Broducten
ByBy			Ті	de	2/20 191
litle	L & GAS INSPECT	15 (13) . L. J	D:	ate	2/36/91

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or ehemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrutbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for previure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the authosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above,
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas sones only) and gravity and GOR (oil zones only).