+ 1/4#/sx Flocele (236 cf). Circ 10 bbls cmt to surf. Test to 1000 psi, 15 min, OK.

1/4 cf/sx Perlite + 1/4#/sx Flocele (178 cf). Tail w/150 sx CL-B (177 cf) + 1/4# Perlite + 1/4#/sx Flocele. Tail w/50 sx (59 cf) CL-B + 1/4#/sx Flocele + 2% CaCl₂. Circ 1 bbl cmt to surface. PT to 1500 psi OK. oue 2

Set @ Valve/Manu. and Type __ Subsurface Salety 18. I hereby certify that the foregoing is true and correct TITLE Production Analystate SIGNED (This space for Federal or State office use) DATE TITLE _ APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

See Instructions on Reverse Side

ACCEPTED FOR RECORD

DEC 0 7 1983

MMOCC

FARMINGTON RESUURCE AREA 5mm1

11/16/83: Reach TD @ 6630'. Run 93 jts (4138') 4-1/2"
10.5# K-55 ST&C csg, set @ 6630', cmt w/305 sx (561cf) 65:35
+ 6% gel + 1/4#/sx Flocele + .6% Halad 9. tail w/150 sx (177 cf)
CL-B + 1/4#/sx Flocele + .6% Halad 9. Circ 10 bbls cmt.
Rig released 11-6-83. PBTD @ 6720. PT to 1000 psi, OK.

A Company