

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1620' FNL & 1010' FEL

RECEIVED

MAY 31 1984

14. PERMIT NO.

15. ELEVATIONS (Show well base, surface, and management
FARMINGTON RESOURCE AREA
8211' GL

5. LEASE DESIGNATION AND SERIAL NO.

SF-078872-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hillside

9. WELL NO.

1E

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 9, T27N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Spud & Casing Report

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

5-25-84

Spudded 12-1/4" surface hole at 10:00 PM 5-25-84 and drilled to
total depth of 225'. Ran 5 joints (202.10') of 8-5/8", 24#, K-55
casing set at 214'. Cemented with 140 sacks (165 cu.ft.) of
Class "B" with 1/4# celloflake per sack and 3% CaCl2. Plug down
at 4:00 AM 5-26-84. Circ 10 bbls cmt to surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

Cather Greyeyes

TITLE

Secretary

DATE

5-29-84

(This space for Federal or State office use)

APPROVED BY

TITLE

ACCEPTED FOR RECORD

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

JUN 06 1984

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY *Snm*