			. /		
Form 3160-5 vovember 1983) Formerly 9-331)	UNITED STATES STATES OF THE INTERIOR TO THE IN	BMIT IN TRIPLICATES ther instructions on re-	Expires Augus	No. 1004-0135	
J. J	BUREAU OF LAND MANAGEMENT		5. LEASE DESIGNATION AND SERIAL NO. SF-078872-A		
	DRY NOTICES AND REPORTS ON W form for proposals to drill or to deepen or plug back to a Use "APPLICATION FOR PERMIT—" for such proposals.)		6. IF INDIAN, ALLOTT	EE OR TRIBE NAME	
OIL GAS WELL	STRIFE XX		7. UNIT AGEREMENT !	AYAR	
2. NAME OF OPERATOR				8. FARM OR LEASE NAME	
	Southland Royalty Company			Frontier "B"	
P.O. Drawer 570, Farmington New Marido Grafe VE			9. WHLL NO. 3E		
4. Location of well (Report location clearly and in accordance with any State requirements.  See also space 17 below.)			10. FIELD AND POOL, OR WILDCAT		
The bulliage		Basin Dakota			
(N) 605' FSL & 1945' FWL BURGAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA		11. SEC., T., R., M., OR RLE. AND SURVEY OR AREA			
14. PERMIT NO.			Section 4,	T27N, R11W	
14. PERRIT NO.	15. ELEVATIONS (Show whether DF, RT. GR, et	چ.)			
<del></del>			San Juan	New Mexico	
16.	Check Appropriate Box To Indicate Nature of	f Notice, Report, or O	ther Data		
	OTICE OF INTENTION TO:	SUBSECUE	INT REPORT OF:		
TEST WATER SHUT-OF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	MULTIPLE COMPLETE FI	ATER SHUT-OFF  MACTURE TREATMENT  HOOTING OR ACIDIZING  Other)  (Note: Report results of Completion or Recomple		CASING X	
17. DESCRIBE PROPOSED OF proposed work. If nent to this work.)	COMPLETED OPERATIONS (Clearly state all pertinent details, well is directionally drilled, give subsurface locations and				
10/16/84	TD 7-7/8" hole at 6750'.				
10/17/84	Ran 157 joints (6736') of 4-1/2", 11.6#, K-55 casing set at 6748'. Cemented 1st Stage with 325 sacks (416 cu.ft.) of Class "B" 50/50 Poz with 2% gel, 10% salt and 1/4# flocele per sack, tailed with 50 sacks (59 cu.ft.) of Class "B" neat cement. Plug down at 11:00 PM 10-17-84. Circulated 4 hrs. Cemented 2nd Stage with 338 sacks (568 cu.f.t) of Class "B" 50/50 Poz with 2% gel, 10% salt, 10% Calseal and 12-1/2# gilsonite per sack, tailed with 50 sacks (59 cu.ft.) of Class "B" cement with 2% CaCl2. Plug down at 3:00 AM 10-18-84. Circulated 4 hrs.				
10/18/84	Cemented 3rd Stage with 385 sacks with 2% gel, 10% salt, 10% Calsea with 50 sacks (59 cu.ft.) of Clas 7:30 AM 10-18-84. Good circulati 10-18-84. Ran temperature surve	(648 cu.ft.) of 1 and 12-1/2# gi s "B" neat with on throughout jo	Class "B" 69 Isonite per 9 2% CaCl2. Pl b. Rel rig 8	5/35 Poz sack, tailed lug down at at 10:00 AM	
	-	**************************************	property services of the servi		

NOY 2 6 1034 certify that the foregoing is true and correct 10/19/84 TITLE Secretary (This space for Federal or State office use) ACCEPTED FOR DECORD APPROVED BY \_ TITLE . CONDITIONS OF APPROVAL, IF ANY: NOV 0 8 18 84