

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR
P. O. Box 3280 Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FNL & 1600' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE SF-078902-A	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME Gallegos Canyon Unit	
8. FARM OR LEASE NAME	
9. WELL NO. 338	
10. FIELD OR WILDCAT NAME West Kutz Pictured Cliffs	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 9 T27N-R12W	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS: (SHOW DF, KDB, AND WD) GL Elev 5740'-K.B. Elev 5748'	

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐
FRACTURE TREAT	☐
SHOOT OR ACIDIZE	☐
REPAIR WELL	☐
PULL OR ALTER CASING	☐
MULTIPLE COMPLETE	☐
CHANGE ZONES	☐
ABANDON*	☐
(other) Well History	☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 16 1984

BUREAU OF LAND MANAGEMENT
WASHINGTON, D. C. 20250

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 9:00 A.M. 11-29-84. Drld 9 7/8" hole to 127' and set 3 jts 7 5/8" 26.40#, K-55, ST&C casing @ 127' K.B. Cemented w/45 sx Class "B" cement w/ 2% CaCL2 + 1/4 Flocele/sx. Plug down 2:00 P.M. 11-29-84. Good cement returns.

Nippled up & pressure tested B.O.P.E. to 500 psi-held O.K.

Drilled 6 1/4" hole to 1456' and ran logs. Ran 38 jts. 10.5#, K-55, 4 1/2" O.D., ST&C casing set @ 1435' K.B. Cemented w/185 sx 50-50 pozmix and cement w/2% gel, 1/2 of 1% CF10, + 1/4# Celloseal/sx. Plug down 3:45 A.M. 12-2-84. Good cement returns.

12-3-84 W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft

18. I hereby certify that the foregoing is true and correct

SIGNED W. D. Thomas TITLE Drilling Foreman DATE 12-6-84

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

(This space for Federal or State office use)

TITLE _____ DATE _____

ACCEPTED FOR RECORD

DEC 28 1984

FARMINGTON RESOURCE AREA

RY *SM*

*See Instructions on Reverse Side