STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: B282710 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:MCADAMS CA B 2E Meter #:95551 RTU:1-136-05 County:SAN JUAN

	NAME RESERVOIR OR POOL			TYPE PROD	METHOD PROD		MEDIUM PROD		
JPR	MCADAMS C	CA B 2E DI	K 9555	1	GAS	FLOW		TBG	
LWR COMP	MCADAMS C	CA B 2E G		5 1-136-5 6) 1-135-5	OIL	ABAND	·	CSG	
	l	PRI			PRESSURE DA	.TA			
	Hour/Date	e Shut-In			e Shut-In	SI Press	. PSIG	Stabi	lzed
UPR COMP	09/27/93 alread	₁ (5I)							
LWR COMP	09/27/93								
			l	FLOW TEST	DATE NO.1			. 1	
Comme	nced at (ho	our,date)*				Zone	Produci	ng (Upr	/Lwr)
TIME (hour, date)		LAPSED TIME SINCE*		PRESSURE Upper Lower		Prod Temp.	REMARKS		
0	9/2व/93	Day	1		262		Bot	h Zones	SI
O	9/2 9 /93	Day	2		250		Bot	h Zones	SI
0	9/29/93	Day	3	4	368		Bot	h Zones	SI
D	9/30/93	Day	4	4	368		11	11	
Þ	0/81/93	Day	5	4	222		Lowe	er Zone	Flau
10/0 2 /93		Day	6	4	£73		/1	• •	. ,
Produ Oil:_ Gas:	ction rate	BOPD	based MFCPD	:Tested t	BBLs in		Gra er):METE		R
UPR COMP	Hour, Dat	e SI Len	gth of	Time SI	SI Press	. PSIG S	Stabiliz	ed (yes	/no)
LWR COMP	-						0012.	1150	1
		I	(Con	tinue on	reverse si	l de)	OIL CO DIS		

FLOW TEST NO. 2

commensed at thour, da	(e) = =			Zone producing (Upper or Lower):		
THRE	LAPSED TIME SINCE ##	PRESSURE		PROD. ZOME		
(hour, date)		Upper Completion	Lewer Completion	TEMP,	REMA	RK8
~ ~~~~	 					
,						
•						
		<u> </u>	<u> </u>	1	<u> </u>	
Production rate d	uring test					-
nit.	P ∩n	D b	nii :	•	Grav	
/II	BOP	D based on	DDIS. IN	Hours	Grav	GOR
as		MCF	PD: Tested thru	(Orifice or Meter	·):	-
				•	,	
emarks:				 		
hereby certify th	at the informati	on herein contain	ed is true and co	mplete to the bes	t of my knowledge.	•
, (OCT 2 1 19	993			Anna Par	
Approved	I Consequerion T	Nivisios	19 (Operator	Thora Vroa	uction comp
THE W MEDICO OF	i Conscivation L	MARION	P	le Su	Amoio brod	rla)
	내려가 되는 것 같습니다.		2	1	011	
Зу	·		Т	itle	Ild Technor	ogest
	The S DAI (NOTE	o co nice ka	_	Date	-18 92	
ide <u>CEPUTY</u>	ヤル ひ しみる 見りとし	UN . L. J. I #4.7	T			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas aones only) and gravity and GOR (oil zones only).