Location of Well: M282710 Fage 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	tor: AMOCO cer #:95483		RTU:	ANY Lease 1-137-05	e/Well #:MC C	CADAMS (County:S	CA B AN JU	1E AN	
	NAME RESE	RVOIR OR F	.00F		TYPE PROD	METHOD	PROD	ME	DIUM PROD
UPR COMP	MCADAMS CA B 1E GP 9221			5	OIL.	FLOI	FLOW		C36
LWR COMP	MCADAMS CA B 1E DK 9548			35	GAS		FLOW		TBG
		PRE	E-FLOW	I SHUT-IN	PRESSURE DA	ATA			. 20. 10. 402 40. 40. 20. 20. 20. 20.
	Hour/Date	Length of Time St		e Shut-In	-In : SI Pr		SIG	Stabilzed	
UPR COMP	1 08/03/92 1 ACWA	<i>γ</i> 5	,	ALWAG	<u> </u>	1	10 405		
COMP	R 08/03/92			72 hrs			271		4.es
Comme	nced at (ho	our,date)*		FLOW TEST	DATE NO.1	. Zon	e Pro	 oducir	ng (Upr/Lwr
 (ho	TIME ur, date)	LAPSED SINCE			ESBURE Lower	Pro		RE	EMARKS
<u> </u>	8/03/92	Day	1	10	243		`	Eoth	. Zones SI
0	8/04/92	Day	2	10	271		:	Both	n Zones SI
0	8/05/92	Day	T.	10	271	:			n Zones SI
0	8/06/92	Day	4	i D	271				
	8/07/92	Day		10	221		1 O	0113	112
	8708792				230				
Produ Oil: Gas:	ction rate		MECE	D:Tested t	ineu (Lrifi	ce or me	eter)	Grav Grav METE:	√ <u>°</u> GOR R
-	and another plants where there where the course storm about the				N PRESSURE				
UPR COMP	{	ļ			S1 Press			() () () ()	ed (yes/no)
LWR COMP	3-3-97	;			27	[1		and the second ready second proper proper and the second terms of
	1	TVIC		ntinue on	reverse si	de)	·		Jan

FLOW TEST NO. 2

TIME (hour, dots)	LAPSED TIME SINCE **	PREI Upper Campletten	Lower Completion	PROD. ZOME TEMP,	REMAR	KS.	
		Upper Completion	Lower Completion	TEMP.	REMAR	KB .	
	1 1				REMARKS		
			.				
			 				
1							
	75		<u> </u>			<u> </u>	
							
<u>-</u>	<u> </u>	<u></u>					
		<i>"</i>		Į ·			
s:		мс	FPD: Tested thru	(Orifice or Meter	r):	 	
marks:	· · · · · · · · · · · · · · · · · · ·				· · · · · · · · · · · · · · · · · · ·		
nereby certify the	hat the informati	ion herein contai	ned is true and o	omplete to the be	st of my knowledge.	n	
					Inoco 8		
proved New Mexico O	il Conservation I	Division	19	Operator	san 11/50	Laucus La	
			1	By	1 1150		
				Title	reld 2	ech	
' 					0-12-92		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or ehemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least "2 hours prior to the commencement of any packer leakage usst, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shot-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven durs.
- 4. For Flow Tex No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such text shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage text, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shot-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same so for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-sone resu must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-missure intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period, 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil some tests: all pressures, throughout the errire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least swice, sace at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as we'll as the flowing a temperatures (gas zones only) and gravity and GOR (oil zones only).