

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
Reverse Side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION RECORD AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		1b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESER. ☐		OCT 15 1985	
2. NAME OF OPERATOR El Paso Natural Gas Company				OIL CON. DIV.	
3. ADDRESS OF OPERATOR P. O. Box 4289, Farmington, NM 87499				RECEIVED	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1610'N, 810'W At top prod. interval reported below At total depth				OCT 08 1985 BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA	
14. PERMIT NO.		DATE ISSUED		12. COUNTY OR PARISH San Juan	
13. STATE NM		15. DATE STUDDED 6-9-85		16. DATE T.D. REACHED 6-14-85	
17. DATE COMPL. (Ready to prod.) 10-4-85		18. ELEVATIONS (DF, RNB, RT, GR, ETC.)* 6067' GL		19. ELEV. CASING HEAD 6067'	
20. TOTAL DEPTH, MD & TVD 4827'		21. PLUG BACK T.D., MD & TVD 4808'		22. IF MULTIPLE COMPL., HOW MANY* One	
23. INTERVALS DRILLED BY Rotary		24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 4522-4502' (Blanco Mesa Verde)		25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN Correlation Gamma-Ray Log; Temp Survey; Formation Density Sidewall Neutron; Ind. Log; Temp. Log; Cyberlook		27. WAS WELL CORED No			
28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	36.0#	231'	12 1/4"	142 cu ft	
7"	20.0#	2300'	8 3/4"	369 cu ft	
29. LINER RECORD					
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	
4 1/2"	2131'	4827'	450 cu ft		
30. TUBING RECORD					
SIZE	DEPTH SET (MD)	PACKER SET (MD)			
2 3/8"	4775'				
31. PERFORATION RECORD (Interval, size and number)					
4420, 4424, 4428, 4432, 4436, 4440, 4444, 4448, 4460, 4465, 4470, 4482, 4487, 4492, 4502, w/1 SPZ. 2nd stage 4522, 4536, 4542, 4556, 4580, 4602, 4620, 4668, 4695, 4702, 4726, 4758, 4777, 4793, w/1 SPZ.					
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED			
4420-4502		67,000# 20/40 sand&92,106 gals treated water			
4522-4793		74,000# 20/40 sand&70,740 gals treated water			
33. PRODUCTION					
DATE FIRST PRODUCTION 8-2-85		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing - Capable of Comm. HC to be tested when connected.		WELL STATUS (Producing or shut-in) Shut in	
DATE OF TEST 10-4-85	HOURS TESTED SI 7 Days	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL. 0	GAS—MCF. 0
WATER—BBL. 0		GAS-OIL RATIO 0			
FLOW. TUBING PRESS. SI 123	CASING PRESSURE SI 578	CALCULATED 24-HOUR RATE	OIL—BBL. No Flow	GAS—MCF. No Flow	WATER—BBL. No Flow
OIL GRAVITY-API (CORR.) 0					
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Shut in to be Sold				TEST WITNESSED BY Bill Huntington	
35. LIST OF ATTACHMENTS Temp Survey					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.					
SIGNED [Signature]		TITLE Drilling Clerk		DATE 10-7-85	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCC

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Chacra	3036'	3710'	Gry fn grn silty, glauconitic sd stone w/drk gry shale
Mesa Verde	3710'	3770'	Gry, fine-grn, dense sil ss., carb sh & coal
Menefee	3770'	4390'	Gry, fine-grn s, carb sh & coal
Point Lookout	4390'	4827'	Gry, very fine sil ss w/frequent sh breaks

38.

GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Chacra Mesa Verde Menefee Point Lookout	3036' 3710' 3770' 4390'	