

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF 078566A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Post Office Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 1830'S, 800'E

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6266' GL

8. FARM OR LEASE NAME

Howell

9. WELL NO.

3A

10. FIELD AND POOL, OR WILDCAT
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 34, T-28-N, R- 8-W
NMPM

12. COUNTY OR PARISH
San Juan

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-20-85

TD 2893'. Ran 69 jts. 7", 20.0#, K-55 intermediate casing, 2880' set @ 2892'. Cemented with 120 sks. Class "B" with 6% gel and 2% calcium chloride, 1/2 cu.ft. Perlite (232 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours, held 1200#/30 min. Top of cement @ 1600'.

7-24-85

TD 5304'. Ran 65 jts. 4 1/2", 10.5#, K-55 casing liner, 2566' set @ 5304'. Float collar set @ 5293'. Top of liner hanger @ 2748'. Cemented with 50 sks. Class "B" 50/50 Poz, 2% gel and 0.6% fluid loss additive (60 cu.ft.) and 285 sks. Class "B" 50/50 Poz with 2% gel, 6.25# gilsonite, 1/4# celophane flake, and 0.6% fluid loss additive (390 cu.ft.) WOC 18 hours. Circulate cement to surface.

RECEIVED

AUG 06 1985

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Clerk

DATE

7-26-85

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

AUG 06 1985

CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.