

5 BLM 1 McHugh 1 Connelly 1 File  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**BUREAU OF LAND MANAGEMENT**  
SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985.

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NOO-C-14-20-7467	
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo	
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87499		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 890' FSL - 890' FWL		8. FARM OR LEASE NAME Lucky Billy Charlie	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 6081' GL		10. FIELD AND POOL, OR WILDCAT Gallegos Gallup Ext.	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 22, T27N, R13W, NMPM	
		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

**RECEIVED**

AUG 27 1985

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON\* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT\* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Spud & Surface Casing ☒

(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

M.I. & R.U. Four Corners Drilling Company rig #3. Spudded a 12 1/4" hole at 2:30 PM on 8-24-85. Drilled to 205'. Ran 6 jts. 8-5/8" OD, 24#, J-55, 8 Rd ST&C casing (T.E. 182.46') set at 195' RKB. Cemented with 135 sacks class "B" plus 2% CaCl<sub>2</sub> (159 cf). Circulated approximately 3 bbls cement to surface. P.O.B. at 6:45 PM 8-24-85.

(Pressure tested BOP and surface casing to 750 psi for 30 minutes - held OK.)

**RECEIVED**  
AUG 29 1985  
OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

8-26-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

1985

\*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA